

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

JAN 7 1972

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

**O. C. C.**

**ARTESIA, OFFICE**

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> <b>Deepen</b>		7. Unit Agreement Name
2. Name of Operator <b>Yates Petroleum Corporation</b>		8. Farm or Lease Name <b>Artesia Airport CP</b>
3. Address of Operator <b>207 South 4th Street - Artesia, New Mexico 88210</b>		9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>M</b> <b>330</b> FEET FROM THE <b>South</b> LINE AND <b>990</b> FEET FROM <b>West</b> <b>11</b> TOWNSHIP <b>17S</b> RANGE <b>25E</b> NMPM.		10. Field and Pool, or Wildcat <b>Wildcat</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3511' GR</b>		12. County <b>Eddy</b>

16.

**Check Appropriate Box To Indicate Nature of Notice, Report or Other Data**

**NOTICE OF INTENTION TO:**

**SUBSEQUENT REPORT OF:**

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOB ☒  
OTHER ☒ **Perforate**

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**OTD - 1540'**

**11-2-71 - Spudded old hole at 11:00 PM 11-2-71.**

**TD 8099'; PBTD 8064'. - Ran 8111' of 4½" casing (615' 11.6#), (1692' 10.5#), (5026' 9.5#), (778' 10.5#) set at 8099'. Centralizers at 7933, 7835, 6995, 6578, 6382 and 5177', 1 - float collar at 8064', basket at 6544, DV tool at 6511'. Cemented with 260 sacks of Class C Incor with 3% salt and 0.5% CFR-2 around shoe, and 150 sacks Pozmix Howco-Lite cement thru DV tool. Hung casing w/25000# Rector Type RH2 casing head. Cut off 21' of casing. WOC 72 hours and tested casing with 2200#. Tested OK.**

**Perforated by Perfojet Services the following interval: 7860-7877' with 24 shots.**

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie L. [Signature] TITLE Engineer DATE 1-6-72

APPROVED BY W. A. Gressett TITLE 3D REP OF WELLBORES DATE 1-6-72

CONDITIONS OF APPROVAL, IF ANY: