

Yater Petroleum Corp. - Federal "CR" #1 - 29-17S-25E
Drill stem Tests:

DST #1 - 6424-6762' - Cisco.

TO 15" - plugged. TO 60", SI 120". Op w/weak
blow. Reopened w/strong blow.

Recovered: 380' DM, no gas.

Pressures: IHP 2969; IFP 302; FFP 302;
FSIP 1760 increasing; FHP 2958. BHT 120 deg.

DST #2 - 6990-7200' - Canyon

TO 15", SI 60", TO 75", SI 5 hrs. MTS in 11", stabilized
750# on 1/4" choke at 1.1 MMCFPD. Recovery - 970'
SMCDM. Sampler - 15.3 cu. ft. gas trace of
Condensate. 2050# - No fluids.

Pressures: IHP 3247; IF 486.618; FF 574-1148;
TSIP 2515; FSIP 2515.

RECEIVED

SEP 25 1973

U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

DST #3 - 7400-7565' - Canyon

TO 15", SI 60", TO 60", SI 120". TO w/weak blow increasing
to fair blow. Reopened w/weak blow & increased
after 35'. Recovered 290' DM. Sampler: 600#, 2500
cc DM. Pressures: IHP 3507; IFP 131-175#;
ISIP 306; FHP 3507; FFP 175-216; FSIP 350. BHT 126 deg.

DST #4 - 7900-8050' - Atoka

TO 15", SI 60", Op 50", SI 120". Op w/good
blow, MTS in 7", 340 psi on 1/4" choke. Increased
to 880 psi in 15" (1.3 MMCFPD). 2nd flow 1820 psi
on 1/4" choke after 60" (2.7 MMCFPD). Rec: 188' DM.
trace of Condensate. Sampler: 1750 psi, 11.9 cu. ft. gas.

Pressures: HP 3861-3728; IFP 805-851; FFP 989-2110;
TSIP 2795; FSIP 2795 - BHT 125 deg