

UNITED STATES <sup>N.M.O.C.D. COPY</sup>  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYForm approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0439900-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "CR"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Richard Knob/Eagle Creek

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 29, T.17S., R.25E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐  
2. NAME OF OPERATOR Yates Petroleum Corporation  
3. ADDRESS OF OPERATOR 207 South 4, Artesia, NM 88210  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface  
660' FSL & 660' FWL Sec. 29, T.17S., R.25E  
14. PERMIT NO.  
15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3612' GR

MAY 27 1980

O.C.D.

ARTESIA, OFFICE

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐  
☐

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☒  
☐  
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) plugback &amp; recomplete

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

☐  
☐  
☐  
☒  
☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Temporarily abandoned Richard Knob Atoka (7944-7964') and Eagle Creek Permo Penn (Canyon 6999-7174') commingled completion as follows:

Set standing valve in packer at 7867' above Atoka. Loaded hole and set retrievable bridge plug @ 7825'. Perforated Strawn zone 7643-49' 7753-58' by wireline. RIH with packer and retrievable bridge plug and separately treated each set of perforations with 1250 gallons of 15% DS 30 acid (total 2500 gallons). After treatment tubing set in packer @ 7604' and retrievable bridge plug @ 7792'. Swabbed well in and flowed to unload fluid. Flow stabilized at 35 psig on 1/2" positive choke (300 MCFGPD).

RECEIVED

MAY 27 1980

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Albert R. Hall*

TITLE Engineer

DATE May 27, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side