

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 110
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gator Petr. Corp.</u>		Lease <u>Bolton Ch. Com.</u>		Well # <u>1</u>	
Location of Well	Unit <u>B</u> <u>660 N</u> <u>2180 E</u>	Section <u>9</u>	Township <u>17</u>	Range <u>26</u>	County <u>Elby</u>
Drilling Contractor <u>Ark Drily Co</u>			Type of Equipment <u>Rotary 7.5 stat 8-27-73</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 3/8"</u>	<u>48</u>		<u>400</u>	<u>line</u>
<u>12 1/4"</u>	<u>8 7/8"</u>	<u>24</u>		<u>1360</u>	<u>line</u>
<u>7 7/8"</u>	<u>4 1/2" to 5 1/2"</u>	<u>10.5 + 11.6</u> <u>15.5 + 17</u>		<u>8300</u>	<u>250</u>

Casing Data:

Surface 41 joints of 8 3/8" inch 24 # Grade API New K-55

(Approved) (Rejected)

Inspected by Edgar Williams date 8-4-73

Cementing Program

Size of hole 12 1/4" 1282 ^{11" 1320} Size of Casing 8 3/8 Sacks cement required 600

Type of Shoe used None Float collar used None Btm 3 jts welded Thread Lock

TD of hole 1320' KB Set 1312' CL Feet of 8 3/8" inch 24 # Grade K-55

New-used csg. @ 1312 with 240 sacks neat cement around shoe 270 cc 4.8
+ 350 / sack Mass C additives 3% Gel, 6% Flocc, 8% Glycerite 2% CC 13.0

Plug down @ 9:25 (AM) (PM) Date 8-4-73

Cement circulated None No. of Sacks None

Cemented by Deaton Witnessed by R. A. Williams

Temp. Survey ran @ 11:00 (AM) (PM) Date 8-4-73 top cement @ 150

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Surface TD 421 TD 17 3/8 hole landed 418' RB, 410' GL
27 1/2 x Increte Neat 4% CC, Circ 15/8 x PD 3:00 PM 8-2-73