

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

HM - 0556811

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brewer

9. WELL NO.

28

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

12 - 16S - 29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL ☐ GAS ☐ WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

General American Oil Company of Texas

3. ADDRESS OF OPERATOR

P. O. Box 416 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface

1980' FSL and 1900' FWL

Sec. 12, T-16S, R-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3735' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plug Back & Temp. Abandon

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

We plugged and temporarily abandoned as follows:

1. Pulled 2" tubing and layed down packer.

2. Went back in hole and spotted 35' cement plug on top of bridge plug from 10,476 back to 10,440.

3. Set 100' plug from 10,200 back to 10,100 then came out of hole with 2" tubing.

4. Rigged up and ran free point and cut 5-1/2" casing off at 6500'.  
Layed down 5-1/2" casing.

5. Ran 2" tubing and set plugs as follows:

100' Plug from 8,000' - 7900'.

100' Plug from 6550' - 6450' (50' in and 50' out of 5-1/2" stub).

100' Plug from 4900' - 4800'.

100' Plug at bottom of 8-5/8" casing (2650'-2750')

Well temporarily abandoned for possible future completion inside 8-5/8" casing which is cemented with 300 sacks from 2699' KB.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Superintendent

DATE October 10, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE WELL MUST

DATE

CONDITIONS OF APPROVAL, IF ANY:

UNLESS FURTHER APPROVED, BE PUT TO BENEFICIAL USE OR PLUGGED BY  
APRIL OCTOBER 1975

See Instructions on Reverse Side

APPROVED  
NOV 27 1974  
H. L. BEEKMAN  
ACTING DISTRICT ENGINEER