

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARRESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates Petr. Corp.</u>		Lessor <u>State C.Y.</u>		Well # <u>1</u>	
Location of Well	Unit <u>1980s+2</u>	Section <u>32</u>	Township <u>17</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>Arb. Drilling Co.</u>		Type of Equipment <u>Rotary</u> to start approx 11-24-73		

APPROVED CASING PROGRAM 11-19-73

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17"	13 3/8"	48		300	135 cu.
12 1/4" n11"	8 5/8"	24		1000	375 cu.
7 7/8"	5 1/2" n 4 1/2"			8500	300

Casing Data:

Surface 26 joints of 2 3/4 inch 4 # Grade H-40 117 Van
(Approved) (Rejected)

Inspected by J. H. Williams date 11-24-73

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required 500

Type of Shoe used Texas Float collar used — Btm 3 jts welded Flt collar

TD of hole 1066 Set 1049 Feet of 8 5/8 Inch 2 1/2 # Grade H-40

New-used csg. @ 1049 with 150 sacks neat cement around shoe 1000 4000

+ 200 sack Van additives 4 1/2 # Flt collar 13 c

Plug down @ 802 (AM) (PM) Date 11-28-73

Cement circulated None No. of Sacks None

Cemented by W. J. Williams Witnessed by J. H. Williams

Temp. Survey ran @ 2:25 (AM) (PM) Date 11-28-73 top cement @ 400'

Casing test @ — (AM) (PM) Date —

Method Used — Witnessed by —

Checked for shut off @ — (AM) (PM) Date —

Method used — Witnessed by —

Remarks: Probs 657 - 1066 - lost zone 700

531 13 3/8 48" H-40 - 208 - 17206

12 5/8 1000 4000 11/28/73 5/94 Plug down 413

11-26-73