

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUN 18 1974

O. C. C.

SUNDRY NOTICES AND REPORTS ON WATERSIA, OFFICE

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Hanson Oil Corporation 3. Address of Operator Box 1515, Roswell, New Mexico 88201 4. Location of Well UNIT LETTER I, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 27 TOWNSHIP 17-S RANGE 26-E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3324	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/> 5. State Oil & Gas Lease No. 7. Unit Agreement Name 8. Farm or Lease Name Big Buck Pounds Comm 9. Well No. #1 10. Field and Pool, or Wildcat Undesignated Morrow 12. County Eddy
--	---

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work; SEE RULE 1103.

5-22-74: Moved in and rigged up rotary, spudded @ 5:15 P.M.
5-25-74: T.D. 510', set 12 3/4 42# casing @ 509' (13 jts) Cemented w/525 sx. Cl. C. cement w/2% C.Cl., Circ. 75 sx., plug down @ 9:50 A.M. W.O.C. 18 hrs., tested to 1000 P.S.I. for 30 min., held O.K.
5-29-74: T.D. 1461', ran 236' of 32# 8 5/8" and 1219' of 28# 8 5/8. Cemented w/285 sx HOCO light w/1/4# Flocel, 5# Gil, & 2% C.Cl. & 200 sx. Cl. C., Circ. cement to surface. Plug down @ 11:00 A.M. W.O.C. 18 hrs., tested to 1500 P.S.I. for 30 min., held O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray W. [Signature] TITLE Vice President-Production DATE 6-3-74

APPROVED BY W. A. Gussett [Signature] TITLE OIL AND GAS INSPECTOR DATE JUN 24 1974

CONDITIONS OF APPROVAL, IF ANY: