

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr Corp.</i>		Lease <i>J. J. J.</i>		Well # <i>7</i>	
Location of Well	Unit <i>1700N 1080C</i>	Section <i>22</i>	Township <i>17</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor <i>Cactus Drilling Co.</i>			Type of Equipment <i>Rotary to start approx 3-25-74</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32.3		300	100 cu
9 7/8"	7"	23.26		1140	350 "
6 1/4"	4 1/2" & 5 1/2"	9.5 + 15.5		1500	100

Casing Data:

Surface 31 joints of 7" inch 23.26# Grade Used J-55
(Approved) (Rejected)

Inspected by J. A. Morris date 3-27-74

Cementing Program

Size of hole 9 7/8" Size of Casing 7" Sacks cement required 475

Type of Shoe used Texas P Float collar used No Btm 5 jts welded 2 Thread Lock

TD of hole 1131' KB Set 1139' feet of 7 Inch 23.26# Grade J-55

New-used csg. @ 1139' with 125 sacks neat cement around shoe class C 2 1/2 cc 14.8
+ 350 sax Class C additives 6 1/2 lb Gypsum 4 # Flocc 2 1/2 cc 130 13.5

Plug down @ 12:15 (AM) (PM) Date 3-27-74

Cement circulated No No. of Sacks None

Cemented by Denton Witnessed by J. A. Morris

Temp. Survey ran @ 5:30 (AM) (PM) Date 3-27-74 top cement @ 4:00

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: One inch Tagged at 6:35 PM top cut 441'

100/64 Class C 4 1/2 cc PD 7:00 PM Got trace of cut. Pulled

6 stands to 159' and mixed 25/64 same line 10/54