

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

APR 12 1974

O. C. C.
ARTESIA, OFFICE

| | |
|--|--|
| 5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/> | |
| 5. State Oil & Gas Lease No. | |
| 7. Unit Agreement Name | |
| 8. Farm or Lease Name J Lazy J | |
| 9. Well No. 8 | |
| 10. Field and Pool, or Wildcat Eagle Creek S.A. | |
| 12. County Eddy | |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

| |
|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> |
| 2. Name of Operator Yates Petroleum Corporation ✓ |
| 3. Address of Operator 207 South 4th Street - Artesia, NM 88210 |
| 4. Location of Well UNIT LETTER J, 2310 FEET FROM THE East LINE AND 2310 FEET FROM THE South LINE, SECTION 22 TOWNSHIP 17S RANGE 25E NMPM. |
| 15. Elevation (Show whether DF, RT, GR, etc.) 3530' GR |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

| | | | |
|--|---|--|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> | CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> | |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-29-74 - Spudded 14-3/4" hole at 2:15 PM 3-29-74.

Drilled to 311' KB. Ran 7jts of 10-3/4" 32#, J-55 new casing (299') set at 311' KB. Cemented with 175 sacks Class C 4% CaCl. PD 7:00 3-29-74. WOC 12 hrs. Drilled cement, reduced hole to 9-7/8" and resumed drilling.

TD 1140'± Ran 29 jts 7" 23 & 26# used casing, 1156', set at 1140' KB. Centralizers at 1016 and 728'. Cemented w/200 sacks Class C mix (6% gilsonite & 1/4# flocele) 2% CaCl + 150 sacks Class C Neat 2% CaCl. Cement circulated. PD 6:30 PM 3-31-74. WOC 18 hrs. Cut off pipe, welded on 7" collar. Nipped up and tested BOP's and casing w/1000#. OK. Drilled cement plug and tested shoe to 500#. OK. Reduced hole to 6 1/4" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie M. Gressett TITLE Engineer DATE 4-11-74

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE APR 15 1974

CONDITIONS OF APPROVAL, IF ANY: