

N. M. & C. C. COPY,
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TRIPLICATE
(Other Instructions on reverse side)Form approved
Budget Bureau No. 42 R1421.
5. LEASE DESIGNATION AND SERIAL NO.
1M 021900-7
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

| | | | |
|--|--|--|--|
| 1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER | | 7. UNIT AGREEMENT NAME | |
| 2. NAME OF OPERATOR Yates Petroleum Corporation | | 8. FARM OR LEASE NAME Federal "BW" | |
| 3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM 88210 | | 9. WELL NO. 5 | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 990' FSL & 2310' FEL of Sec. 22-17S-25E | | 10. FIELD AND POOL, OR WILDCAT Eagle Creek S.A. | |
| 14. PERMIT NO. | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 22-17S-25E | |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3528' GR | | 12. COUNTY OR PARISH Eddy | |
| | | 13. STATE NM | |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & set 10-3/4" csg.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-18-74 - Spudded 3:00 PM 4-18-74.

TD 222' - Drilled 14 1/2" hole to 222'. Ran 5 jts of 10-3/4" 30#, J-55 new casing set at 222' w/150 sx Class C 4% CaCl cement. PD 10:00 PM 4-18-74. Cement circulated. WOC 12 hrs, backed off landing jt, drilled cement and reduced hole to 9-7/8" and resumed drilling.

TD 1153' - Ran 38 jts of 7" 23#, J-55 used casing (1157') set at 1153'. Centralizers at 1057 and 723', baskets at 723' and 1-Guide Shoe. Cemented w/200 sx Incor Mix (6% gilsonite, 1/4# flocele) 2% CaCl and 150 sx Class C Neat 2% CaCl. PD 4:00 PM 4-20-74. Cement circulated. WOC 18 hours cut off casing and nipped up. Tested BOP's and casing to 1000#. OK. Drilled plug and tested shoe to 500#. OK. Reduced hole to 6 1/4" and resumed drilling.

RECEIVED

MAY - 3 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE 5-3-74

(This space for Federal or State office use)

APPROVED BY

DISTRICT ENGINEER

TITLE

DATE

MAY 7 1974

CONDITIONS OF APPROVAL, IF ANY: