

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr Corp</i>		Lease <i>Grey</i>		Well # <i>2</i>	
Location of Well	Unit <i>23105 330W</i>	Section <i>13</i>	Township <i>17</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor	<i>Cactus Drilling Co.</i>		Type of Equipment <i>Rotary to start approx. 4-27-74</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>14 1/2"</i>	<i>10 3/4"</i>	<i>30</i>		<i>300</i>	<i>200 cu.</i>
<i>9 1/2"</i>	<i>7"</i>	<i>23</i>		<i>1200</i>	<i>400 "</i>
<i>4 1/2"</i> <i>6 1/4"</i>	<i>4 1/2" + 5 1/2"</i>	<i>9.5 + 15"</i>		<i>1500</i>	<i>125 "</i>

Casing Data:
Int.
~~Surface~~ *37* joints of *7"* inch *23, 24 #* Grade *J-55 N-50*
(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole *9 3/8"* Size of Casing *7"* Sacks cement required *500*

Type of Shoe used *Texas P.H.* Float collar used *B.H.H.* Btm *2* jts ~~welded~~ *Thread Lock*

TD of hole *1192 KB* Set *1180* Feet of *7" Inch* *Same* # Grade *J-55 N-50*

New-used csg. @ *1180* *GA* with *150* sacks neat cement around shoe *Class C 2 1/2 cc 4.5*
+ *350* *sax* *Class C* additives *6 1/2 lbs. nitro 1 lb. 2 1/2 cc 13.0*

Plug down @ *6:30* (AM) (PM) Date *4-29-74*

Cement circulated *No* No. of Sacks *No.*

Cemented by *Denton* Witnessed by *L.A. Williams*

Temp. Survey ran @ *12:45* (AM) (PM) Date *4-30-74* top cement @ *6:50'*

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: *1" to 336. Would not go any further. Cut 100/sx Class C 4 1/2 cc PD 2:10 AM*

1" to 315' cut 125/sx Class C 4 1/2 cc Circ 5 1/2 x

* *Surface, Spud 4-27-74 9:00 PM 8 1/2" 32" 14 3/4" 10 1/2"*

337 KB Set 325 Cut 175/sx Class C 4 1/2 cc Circ 30/sx PD 2:30 AM

4-30-74