

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

MAY 8 1974

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1. OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER <input type="checkbox"/> D. C. C. ARTESIA. OFFICE		5. State Oil & Gas Lease No.
2. Name of Operator Yates Petroleum Corporation		7. Unit Agreement Name
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		8. Farm or Lease Name Frey
4. Location of Well UNIT LETTER L 330 FEET FROM THE West LINE AND 2310 FEET FROM THE South LINE, SECTION 13 TOWNSHIP 17S RANGE 25E NMPM.		9. Well No. 2
15. Elevation (Show whether DF, RT, GR, etc.) 3465' GR		10. Field and Pool, or Wildcat Und Eagle Creek S.A.
		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-27-74 - Spudded 14 3/4" hole at 9:00 PM 4-27-74.
TD 337' - Ran 8 jts of 10-3/4" 32#, J-55 casing (325') set at 337' w/175 sx of Class C 4% CaCl. PD 2:30 AM 4-28-74. Cement circulated. WOC 12 hours, backed off landing jt and drilled cement plug, reduced hole to 9-7/8" & resumed drilling.
TD 1192' - Ran 37 jts 7" 23# & 26E, J-55 and N-80 used casing (1179') set at 1191' KB, 1-Tex. Pattern Shoe, centralizers at 1091' & 661', baskets at 693 and 630'. Cemented w/350 sx Incor mix (6% gilsonite 0.6% flocele) 2% CaCl followed w/150 sx Class C 2% CaCl. PD 6:30 PM 4-29-74. WOC 6 hrs and ran Temperature Survey, tagged top of cement at 347'. Spotted 100 sx Class C 4% CaCl at 336'. WOC 3 1/2 hours, tagged top of cement at 315'. Spotted 125 sx Class C 4% CaCl. Cement circulated. PD 6:20 AM 4-30-74. WOC 20 hrs. Backed off landing jt, nipples up and tested BOP's and casing to 1000#. OK. Drilled plug and tested shoe to 500#./ Reduced hole to 6 1/4" and resumed drilling.
OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie M. Kately TITLE Engineer DATE 5-7-74

APPROVED BY W. A. Gessert TITLE OIL AND GAS INSPECTOR DATE MAY 10 1974

CONDITIONS OF APPROVAL, IF ANY: