

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr. Corp.</i>		Lease <i>Holt D L Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980N+W</i>	Section <i>12</i>	Township <i>17</i>	Range <i>26</i>	County <i>El Paso</i>
Drilling Contractor	<i>Art Dugan</i>		Type of Equipment <i>Rotary to start approx. 5-6-74</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17</i>	<i>13 7/8"</i>	<i>48</i>		<i>300</i>	<i>200 cms</i>
<i>12 1/4" 11"</i>	<i>8 7/8"</i>	<i>24</i>		<i>1400</i>	<i>500 "</i>
<i>7 7/8"</i>	<i>5 1/2" 4 1/2"</i>			<i>9200</i>	

Casing Data:

Surface *4 1/2* joints of *2 1/2* inch *24* # Grade *API New STC K-55*
(Approved) (Rejected)

Inspected by *L. A. McMein* date *5-21-74*

Cementing Program

Size of hole *12 1/4* Size of Casing *8 7/8* Sacks cement required *500*

Type of Shoe used *Guide* Float collar used *None* Btm *3* jts welded *Yes*

TD of hole *14200* Set *1403* Feet of *8 7/8* inch *24* # Grade *K-55*

New-used csg. @ *1403* with *150* sacks neat cement around shoe *Class C 28% CC 14.8*
+ *350* sack *Heater* additives *60 lb 2 1/2" 2% CC 13.0*

Plug down @ *1950* (AM) (PM) Date *5-22-74*

Cement circulated *NO* No. of Sacks *1*

Cemented by *Halliburton* Witnessed by *L. A. McMein*

Temp. Survey ran @ *2:00* (AM) (PM) Date *5-22-74* Top cement @ *150*

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *Spud 7:00 AM 5-20-74 17 1/2" hole TD 521 KB*

14 jts 13 7/8 48 K-55 Set 513, Cont 285/sk Class C 4% CC

PD 5:15 PM 5-20-74 Circ. 3/5K