

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

Southeastern New Mexico

Northwestern New Mexico

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	250	250	Caliche & gravel				
250	521	271	Red bed				
521	1409	888	Red bed, anhy & sand				
1409	1492	83	Red bed and anhy				
1492	4628	3136	Lime				
4628	6750	2122	Lime and shale				
6750	6840	90	Lime				
6840	6884	44	Shale				
6884	7007	123	Lime				
7007	8960	1953	Lime and shale				
DST #1	8600-8820'						
TO 30", SI 60", TO 3 hrs, SI 6 hrs. OP w/weak blow. Re-OP w/weak blow, increasing to good in 20". GTS in 93" into final flow. SI 6 hrs. Recovered 552' DM, 224' HGCM.							
Pressures:							
HP 410-4075							
IFP 103-137							
ISIP 3454							
FFP 343 (approx) 308							
FSIP 703							