

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

OCT 31 1975

1. NO. COPIES RECEIVED		3
DISTRIBUTION		
SANTA FE		1
FILE		1
U.S.G.S.		
LAND	FICE	
OPER	OR	1

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A WELL. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

D. C. C.
ARTESIA OFFICE

6. Indicate Type of Well Oil <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
8. Name of Operator Yates Petroleum Corporation		9. Form or Lease Name Gissler "AV"
3. Address of Operator 207 South 4th Street-Artesia, NM 88210		9. Well No. H //
4. Location of Well UNIT LETTER M 330 FEET FROM THE West LINE AND 990 FEET FROM THE South LINE, SECTION 23 TOWNSHIP 17S RANGE 25E N.M.P.M.		10. Field or Pool, or Wildcat Eagle Creek S.A.
15. Elevation (Show whether DF, RT, GF, etc.) 3510' GR		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING Casing <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

Spudded 15" hole at 4:00 PM 10-24-75.
TD 306' - Ran 7 joints of 10-3/4" 32#, J-55 casing (296') set at 306' KB.
Cemented w/200 sacks of Class C 4% CaCl. Cement circulated. PD 7:30 AM 10-25-75.

TD 1154' - Ran 30 joints of 7" 20# K-55 new casing (1154') set at 1153' KB w/2centralizers and 2 baskets at 729 and 648', 1-Tex Pattern notched shoe and cemented w/350 sacks Incor mix + 150 sacks of Class C 2% CaCl. PD 8:25 AM 10-27-75. Cement did not circulate. WOC 6 hours. Ran Temperature Survey had good cement at 720', poor cement at 600'. Ran 1" tubing to 480', unable to wash below 480', spotted 125 sacks of Class C 4% CaCl. PD 5:30 PM 10-27-75. WOC 3 hours and tagged cement at 365', spotted 125 sacks of Class C 4% CaCl. Did not circulate. PD 9:00 PM 10-27-75. WOC 3 hours tagged cement at 336'. Spotted 75 sacks of Class C 4% CaCl. PD 12:30 AM 10-28-75. WOC 2 1/2 hours and tagged cement at 281', spotted 80 sacks of Class C 4% CaCl. PD 3:30 AM 10-28-75. Cement circulated. WOC 18 hrs. Tacked 7" to 10-3/4", cut off lndg. & wldg on collars. NU tstd BOP to 1000#.OK.Drld plg & tstd to 600#.OK. & resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Christine Tomlinson</u>	TITLE <u>Geol Secty</u>	DATE <u>10-29-75</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>OCT 31 1975</u>
CONDITIONS OF APPROVAL, IF ANY:		