

COPIES RECEIVED	
TRIBUTION	
FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 12 1974

O. C. C.  
ARTESIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Powell "DG" Com
9. Well No. 1
10. Field and Pool, or Wildcat Unit West Atoka Morrow
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 South 4th Street - Artesia, NM 88210
4. Location of Well UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 17S RANGE 25E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3490'

6.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOB ☒  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-14-74 - Spudded 17½" hole at 8:30 PM 6-14-74.

TD 391' - Ran 13 jts of 13-3/8" 48#, J-55 (404') of csg. set at 391'. Cmt'd w/250 sx Class C 4% CaCl. PD 9:30 PM 6-15-74. Formation broke and cmt fell behind casing. Filled hole w/4 yds of Ready-Mix. WOC 14½ hrs, drilled plug and reduced hole to 12½" and resumed drilling.

TD 1238' - Ran 34 jts of 8-5/8" 24#, J-55 new casing (1240') set at 1238' KB. Centralizers at 1113 & 700', baskets 741 & 667', 1-Guide shoe. Cemented w/350 sx Incor mix plus 200 sx Class C 2% CaCl. PD 11:40 AM 6-18-74. WOC 6 hrs and ran Temp. Survey, found top of cmt. at 575'. Ran 1" tbg, washed to 420-483' & sptd 100 sx of Class C 4% CaCl. PD 8:40 PM 6-18-74. WOC 2½ hrs. & tagged cmt at 431'. Sptd 150 sx Class C 4% CaCl (w/40# fiber). PD 11:50 PM 6-18-74. WOC 2½ hrs, tagged cmt at 410'. Sptd 250 sx Class C 4% CaCl. PD 3:15 AM 6-19-74. WOC 3½ hrs, tagged cmt at 408. Sptd 50 sx Class C 4% (40# fiber) Cmt. circulated. JC 7:30 AM 6-19-74. WOC 31 hrs. LU & tested EOP's and csg to 1000#. OK. Drilled plug and tested plug to 500#. OK. Reduced hole to 7-7/8" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie L. Lively TITLE Engineer DATE 7-11-74

APPROVED BY W. C. Swartz TITLE OIL AND GAS INSPECTOR DATE JUL 12 1974

CONDITIONS OF APPROVAL, IF ANY: