

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLI
(Other instructions on re-
verse side)Form approved,
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 094404

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "B"

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Bagle Creek S.A.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 27-17S-25E
Unit B

12. COUNTY OR PARISH

Hidalgo

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☐ OIL
WELL ☐ GAS
WELL ☐ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street-Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface 330' FNL & 330' FWL of Sec. 27-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3546' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

TD 1472' - Ran 25 jts of 4½" (809') 9.5#, J-55 and 16 jts 5½" 15.5#
K-55 (654')(1463') casing, 1-4½" Howco shoe, 5 centralizers at 1432,
1392, 1352, 1312, 1272'. Cemented at 1472' w/125 sx of Class C Cement
PD 6:30 PM 6-18-74. WOC 18 hrs and tested to 1000# . CK.
Perforated w/35 .45" jet shots as follows: 1299, 1323, 1341, 1347, 1351,
1354½, 1358, 1361, 1367½, 1377, 1381½, 1385, 1390, 1394, 1398, 1408,
1413, 1297, 1324½, 1343, 1349, 1353, 1356, 1359½, 1369, 1379, 1383, 1387½,
1392, 1396, 1400, 1410, 1415, 1430'.
Sand frac'd using 3000 gallong 15% acid for breakdown, 64000# 20-40
sand and 15000# 10-20 sand and 80000 gallons of treated water.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

6-23-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 28 1974

K. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side