

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPL
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 028755(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Gas Injection

2. NAME OF OPERATOR
Cities Service Oil Company ✓

3. ADDRESS OF OPERATOR
Box 1919 - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

990' FSL & 1880' FWL of Sec. 35-T17S-R27E, Eddy Co., New Mexico

JAN 21 1975

O. C. C.
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME
Citgo Empire Abo Unit

8. FARM OR LEASE NAME

Tract 1

9. WELL NO.

11

10. FIELD AND POOL, OR WILDCAT

Empire Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 35-T17S-R27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3626' GR

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set and cementing 4-1/2" Csg. X
(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 5600' Lime and Dolomite. Waiting on completion unit. Drilled to a T.D. of 5600' and ran 150-1/2 Jts. (5590.00') 4-1/2" OD 10.79# casing set and cemented @ 5600' w/400 sacks Halliburton Lite w/1/4# Flocele, 0.2% GFR-2 and 5# salt/sack followed by 300 sacks Class C w/2% CaCl cement. Plug down @ 11:35 PM on 1-10-75. Bumped float with 1800# - Held O.K. WOC 6 Hrs. Ran Temp. Survey. Top of cement @ 2090'.

RECEIVED

JAN 16 1975
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO
January 14, 1975

18. I hereby certify that the foregoing is true and correct

SIGNED

ORIGINAL SIGNED
BY E. Y. WILDER

TITLE

Region Operation Manager

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JAN 20 1975
R. L. BEEKING
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side