

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Corp. DIV-Dist. 2  
1301 W. Grand Avenue  
Artesia, NM 88210

FORM APPROVED  
Bureau No. 1004-0135  
Expires: March 31, 1993  
Lease Designation and Serial No.  
LC 028755A

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other  
2. Name of Operator  
B.P. (Arco Permian)  
3. Address and Telephone No.  
PO Box 129 Artesia NM 88210 505-392-8064  
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Unit Letter N 990' FSL & 1880' FWL  
Sec 35 T 17 S R 27 E

7. If Unit or CA, Agreement Designation

NM-70925

8. Well Name and No.

Riverwolf # 11

9. API Well No.

30-015-21358

10. Field and Pool, or Exploratory Area

ABO

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-5-02 Plug # 1 Set CIBP @ 5400'

Plug # 2 Spot 25 sks of cement @ 5400'

CIRC. well with mud laden fluid

Plug # 3 Spot 25 sks of cement @ 3150' WOC & Tag @ 2990'

Plug # 4 Perf @ 1060' SQZ 25 sks of cement WOC & Tag @ 1008'

6-6-02 Perf @ 1006'

6-7-02 Plug # 5 Circ. annulus to surface with 220 sks of cement WOC & Tag @ 774'

Plug # 6 Spot 5 sks of cement @ 65' to surface

6-7-02 Cut off wellhead & anchors 3' BGL Install dry hole marker. Backfill & clean location

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed *[Signature]*  
(This space for Federal or State office use)

Title *P&A Manager*

Date 6-18-02

Approved by  
Conditions of approval, if any:

(ORIG. SGD.) ALEXIS C. SWOBODA

Title

PETROLEUM ENGINEER

Date

JUN 25 2002

WELL NAME & NO. RIVERWOLF #1  
 DATE 4/29/02

→ KB-10'

# LEGAL description

API # 30-015-21358

UNIT LETTER N, 990' FSL & 1880' FWL

SECTION 35, T17S, R27E

Eddy County N.M.

Perf'd 4 1/2" CSG @ 1006' + CIRC.  
 ANNULUS to surface w/ 220 SX CEMENT.  
 W.C. + Tag @ 774'

← Perf 4 1/2" CSG @ 61' + CIRC.  
 4 1/2" + 8 5/8" CSG. w/ cement to  
 surface

→ 8 5/8" - 24"  
 K55 STC B JR  
 CIRCULATE CEMENT TO SURF  
 525 SX CEMENT

→ 1010'

Perf 4 1/2" @ 1060' + squeeze a  
 25 SX cement plug from 1060 to  
 1008 + TAG

25 SX cement Plug @ 3150  
 TAG

TOC @ 2090'  
 700 SX

CSG  
 4 1/2"  
 10.79#  
 8R LTC  
 9R A CSG

← 5382 CIBP w/ 25 SX cement  
 → 5482'  
 → 5532'

→ PSTD @ 5556'  
 TOC @ 5600'

| CSG -  | WEIGHT - | DEPT - | HOLE SIZE - | CEMENT PERMITS | TOC / APPROX |
|--------|----------|--------|-------------|----------------|--------------|
| 8 5/8" | 24 #     | 1010'  | 12 1/4"     | 535 SX         | CIRCULATED   |
| 4 1/2" | 10.79 #  | 5600'  | 7 7/8"      | 700 SX         | TC @ 2090'   |

P + A well Bore