

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0439900

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "CB"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Eagle Creek S.A.

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREASec. 15-17S-25E
Unit K NMPM

12. COUNTY OR PARISH

Eddy

NM

1. OIL ☒ GAS ☐ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1650' FSL & 2310' FWL of Sec. 15-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3540' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-27-74 - Spudded 14-3/4" hole at 9:30 PM 9-27-74.

TD 256' - Ran 7 jts of 10-3/4" 30#, K-55 casing (243') set at 256' KB w/150 sacks of Class C 4% CaCl. Cement circulated. PD 4:15 AM 9-28-74.

WOC 12 hours, drilled cement, reduced hole to 9 1/2" and resumed drilling.

TD 1116' - Ran 35 jts of 23#, J-55 used casing (1104') set at 1116' KB.

Centralizers at 1020 and 668', baskets at 699 and 636', 1-TEX Pattern shoe. Cemented w/350 sacks Incor mix (6% gilsonite, 6/10% flocele) 2% CaCl plus 100 sacks of Class C 2% CaCl. PD 4:45 PM 9-29-74. No returns.

WOC 6 hours, ran Temperature Survey, found top of cement at 850'. Ran 1" tubing. Spotted 75 sacks Class C 4% CaCl at 610'. PD 1:00 AM 9-30-74.

WOC 3 hours, tagged cement at 505'. Spotted 100 sacks of Class C 4% CaCl. PD 4:25 AM 9-30-74. WOC 3 1/4 hours, tagged cement at 430'. Spotted 75 sacks Class C 4% CaCl. PD 8:10 AM 9-30-74. WOC 3 hours. Tagged cement at 390'.

Spotted 75 sacks Class C w/0.6% flocele 4% CaCl. PD 11:20 AM 9-30-74. WOC 1 hour, spotted 100 sackd Class C 4% CaCl, filled hole w/4 yards of Ready-mix. JC 12:30 PM 9-30-74. WOC 24 hours, NU, tested casing w/1000#, drilled cement and tested shoe to 500#. OK. Redrilled to 6 1/4" and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

Eddison Melchior

TITLE

Engineer

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

DATE 10-22-74

(This space for Federal or State office use)

APPROVED BY

COMMISSIONER OF APPROVAL, IF ANY:

TITLE

DATE

OCT 22 1974
L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side