

COPIES RECEIVED	2
TRIBUTION	
FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

MAR 5 1975

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Artesia Airport CF
9. Well No. 2
10. Field and Pool, or Wildcat Undesignated
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT L-1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 So. 4th St., Artesia, New Mexico 88210
4. Location of Well UNIT LETTER I 860 FEET FROM THE East LINE AND 1650 FEET FROM THE South LINE, SECTION 10 TOWNSHIP 17S RANGE 25E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3523' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to plug and abandon this well. Present perforations are at 5200-06', 5254-56', 5262-66', tested 25 MCFPD and decreasing.
Propose: to set CIBP at 5150' w/10' cement on top;
cut off 4½" casing at 4740' and recover;
spot 35 sx cement plug at 4350-4250' (across top of Abo);
spot 35 sx cmt plug at 2030-1930' (across Glorietta);
set retainer in 8 5/8" casing at 1100' and squeeze w/50 sx cmt;
set 10' cement and marker at surface.

NOTE: WITNESSED THE FOLLOWING - CLASS C CMT W/2% CAH₂ PLUGS:
35 SX 4330'-4230' IN PLACE @ 2:42 PM - 3-7-75
35 SX 2030'-1930' " " " " 10:42 AM - 3-7-75
SET 8 5/8" GILBERTSON CMT RETAINER @ 1087' @ 12:15 PM - 3-7-75
PUMP IN 75 SX OF WHICH 5 SX LEFT AT CMT RETAINER - @ 12:21 PM - 3-7-75
SET WIRELINE 8 5/8" CIBP @ 1061'
35 SX 700'-600' IN PLACE @ 2:42 PM 3-7-75

Longbottom

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie M. Kelsper TITLE Engineer DATE March 5, 1975

APPROVED BY W. J. Gressett TITLE SUPERVISOR, DISTRICT II DATE MAR 6 1975

CONDITIONS OF APPROVAL, IF ANY:
Intervals between plugs filled w/- mud
Notify N.M.O.C.C. in sufficient time to witness
plugging