

COPIES RECEIVED	
TRIBUTION	
FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
MAR 12 1975

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓		8. Farm or Lease Name Artesia Airport "CF"
3. Address of Operator 207 South 4th Street - Artesia, New Mexico 88210		9. Well No. 2
4. Location of Well UNIT LETTER I 860 FEET FROM THE East LINE AND 1650 FEET FROM THE South LINE, SECTION 10 TOWNSHIP 17S RANGE 25E NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3523' GR		12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒
☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plug and Abandon as follows:

Set CIBP at 5150' w/10' cement on top. Cut off 4½" casing at 4538' and recovered. Spotted 35 sx cement plug at 4350-4250' (across top of Abo); Spot 35 sx cement plug at 2030-1930' (across Gloreitta). Set retainer in 8-5/8" casing at 1084' and squeezed w/50 sx of cement Dumped 1 sx of cement on top of retainer. Set CIBP at 1050'. Spotted 35 sxs of cement at 700'. 10 sx at surface with dry hole marker. Heavy place between each plug.
The location will be cleaned and levelled, pits filled and we will notify your office when the location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie G. Crutcher TITLE Engineer DATE 3-11-75

APPROVED BY Alan Morris TITLE SUPERVISOR, DISTRICT II DATE JUN 6 1975

CONDITIONS OF APPROVAL, IF ANY: