

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
B-2175

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

OIL WELL ☐ GAS WELL ☐ OTHER- P&A

Name of Operator
Yates Petroleum Corporation
Address of Operator
207 South 4th St., Artesia, NM 88210
Location of Well

JUL 10 1981
O. C. D.
ARTESIA OFFICE

7. Unit Agreement Name
8. Farm or Lease Name
Marco Polo EA State
9. Well No.
1

UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM
THE East LINE, SECTION 32 TOWNSHIP 16S RANGE 30E NMPM.

10. Field and Pool, or Wildcat
West Henshaw Wolfcamp

15. Elevation (Show whether DF, RT, GR, etc.)
3732' GR = 3849' KB

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled 8200' of 4-1/2" casing. Set cement plugs as follows:

Plug #1 8250-8150' w/35 sacks Class C cement across 4-1/2" stub
Plug #2 7650-7550' w/35 sacks Class C cement
Plug #3 6450-6350' w/35 sacks Class C cement
Plug #4 4400-4300' w/35 sacks Class C cement
Plug #5 3250-3100' w/45 sacks Class C cement

Ran free point on 8-5/8" casing. Found free point 300' from surface. Did not cut 8-5/8" casing as per verbal approval. Shot squeeze hole at 1275' (2 .50" holes). WIH w/Baker cement retainer @1200'. Squeezed w/75 sacks Class C. Pulled tubing. Shot 2 squeeze holes at 550'. Squeezed w/75 sacks Class C cement from 500'. Spotted 15 sacks surface plug. Installed dry hole marker.

17. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Michael J. Carroll

TITLE Engineering Secretary

DATE 7/10/81

APPROVED BY Mark Stuppfield

TITLE OIL AND GAS INSPECTOR

DATE JUL 27 1982

CONDITIONS OF APPROVAL, IF ANY: