

INSTRUCTIONS

This form is to be filled with the appropriate data by the Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-actively logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon <u>7442</u>	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>7892</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>8272</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>1000</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzite _____
T. Glorieta <u>2385</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>4371</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp <u>5476</u>	T. Morrow <u>8456</u>	T. Chinle _____	T. _____
T. Penn. _____	T. Chester <u>8723</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	490	490'	Surface, gravel & rock				
490	620	130	Red bed & sand				
620	1093	473	Sand				
1093	1500	407	Red bed and sand				
1500	2121	621	Lime				
2121	2674	553	Anhy				
2674	3183	509	Anhy and lime				
3183	4000	817	Lime				
4000	4934	934	Lime and Anhy				
4934	7490	2556	Lime				
7490	7928	438	Lime and sand				
7928	8830	902	Lime and Shale				