

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Marble Energy Corp.</u>		Lease <u>Delhi</u>		Well # <u>ST 3</u>	
Location of Well	Unit <u>N</u>	Section <u>28</u>	Township <u>17</u>	Range <u>28</u>	County <u>Eddy</u>
Drilling Contractor	<u>Jenkins</u>		Type of Equipment <u>Cable Tools</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>10"</u>		<u>225'</u>			
<u>8"</u>		<u>493'</u>			
<u>7"</u>		<u>TD 795</u>			

Casing Data:

Surface 27 joints of 4 1/2" inch 10.5 # Grade K-55  
(Approved) (Rejected)

Inspected by L. Mennis date 2-27-75

Cementing Program

Size of hole 10", 8", 7" Size of Casing 4 1/2" Sacks cement required 200/sx  
Type of Shoe used None Float collar used Insert Btm 2 jts welded Thread Lock  
TD of hole 795 KB Set 793.6 Feet of 4 1/2 Inch 10.5 # Grade K-55  
New-used csg. @ 793 with 100/sx sacks neat cement around shoe Class C 5# Salt 14.5  
+ 100 sax Howe Lite additives 12.8  
Plug down @ 10:00 (AM) (PM) Date 2-27-75  
Cement circulated Yes No. of Sacks 266 1/2  
Cemented by Halliburton Witnessed by L. A. Mennis  
Temp. Survey ran @ (AM) (PM) Date top cement @  
Casing test @ (AM) (PM) Date  
Method Used Witnessed by  
Checked for shut off @ (AM) (PM) Date  
Method used Witnessed by  
Remarks: