

COPIES RECEIVED		
TRIBUTION		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

APR 17 1975

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Berry "EE" Com
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>M</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM <u>West</u> LINE, SECTION <u>23</u> TOWNSHIP <u>17S</u> RANGE <u>26E</u> NMPM.	10. Field and Pool, or Willcat Und Kennedy-Farms Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3320' GR	12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER <u>Set 4 1/2" production casing</u> <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD - DTD 8785'; LTD 8807; WLTD 8625'.

Ran 71 joints of 4 1/2" 11.6# K-55 LT&C (2351'); 115 jts of 4 1/2" 10.5# K-55 LT&C (4790'); 45 jts 4 1/2" 11.6# K-55 LT&C (1520') (Total 8667'), shoe at 8685'; Float collar 8648'. Centralizers at 8615, 8649, 8450, 8324, 8004, 7683'. Washed w/500 gallons mud flush and cemented w/180 sacks Class "H" 3/4% CFR-2, 5# KCL, displaced w/40 bbls 2% KCL + 99 bbls fresh water. PD 9:15 AM 4-3-75. Tested to 1800 psi. OK. Removed BOP's and hung casing on slips. WOC 12 hours and ran Temperature Survey. Top of cement at 8090'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie L. Kelly TITLE Engineer DATE 4-16-75

APPROVED BY W. A. Gressitt TITLE SUPERVISOR, DISTRICT II DATE APR 18 1975

CONDITIONS OF APPROVAL, IF ANY: