

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____ T. Canyon 7470
T. Salt _____ T. Strawn 7934
B. Salt _____ T. Atoka 8320
T. Yates _____ T. Miss _____
T. 7 Rivers _____ T. Devonian _____
T. Queen _____ T. Silurian _____
T. Grayburg _____ T. Montoya _____
T. San Andres 1000 T. Simpson _____
T. Glorieta 2356 T. McKee _____
T. Paddock _____ T. Ellenburger _____
T. Blinebry _____ T. Gr. Wash _____
T. Tubb _____ T. Granite _____
T. Drinkard _____ T. Delaware Sand _____
T. Abo 4391 T. Bone Springs _____
T. Wolfcamp 5578 T. Morrow Clastic 8519
T. Penn. _____ T. Chester 8740
T. Cisco (Bough C) _____ T. _____

Northwestern New Mexico

T. Ojo Alamo _____ T. Penn. "B" _____
T. Kirtland-Fruitland _____ T. Penn. "C" _____
T. Pictured Cliffs _____ T. Penn. "D" _____
T. Cliff House _____ T. Leadville _____
T. Menefee _____ T. Madison _____
T. Point Lookout _____ T. Elbert _____
T. Mancos _____ T. McCracken _____
T. Gallup _____ T. Ignacio Qtzite _____
Base Greenhorn _____ T. Granite _____
T. Dakota _____ T. _____
T. Morrison _____ T. _____
T. Todilto _____ T. _____
T. Entrada _____ T. _____
T. Wingate _____ T. _____
T. Chinle _____ T. _____
T. Pennian _____ T. _____
T. Penn. "A" _____ T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	268	268	Surface	DST #1 -	8431-8550'		(Morrow)
268	470	202	Surface & rock	TO 30", SI 90", OP 90", SI 240"			
470	1460	990	Red bed, anhy & sd	Op w/wk blo, incrd to strong blo, off			
1460	2231	771	Lime	bucket in 3". Incrd to 20# air blo on			
2231	2789	558	Lime and sand	1/8" ch. in 30". GTS in 45". Re-op			
2789	4340	1551	Lime	w/strong blo 35# on 1/4" ch, decrd			
4340	4690	350	Lime and shale	to 24# on 1/4" ch. in 1 hr. then incrd			
4690	5375	685	Lime and sand	slowly on 1/4" ch at end of 2nd flo.			
5375	5777	402	Lime	Recovered: - 390' CGM. BHT 140 deg.			
5777	6830	1053	Lime and shale	Sampler: - 100#, 10.39 cfg, 400 cc mud.			
6830	6914	84	Lime	Pressures: - HP 4096-4083; IFP 174-			
6914	7468	555	Lime and shale	201; ISIP 3207; FFP 174-174; FSIP			
7468	7756	288	Lime	3483.			
7756	8520	764	Lime & shale				
8520	8550	29	Sand				
8550	8580	30	Lime, shale & sand				
8580	8624	44	Lime				
8624	8735	111	Lime & sand				
8735	8785	50	Lime and shale				