SUBMIT IN T ICATE* November 1983) formerly 9-331C) UNITED STATES NA (Other instructions on reverse side) Form approved. C(S) Budget Bureau No. 1004-0136 Expires August 31, 1985 5. LEASE DEBIGNATION AND SEBIAL NO. NM 19673							31, 1985 and seeial no.
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 1a. TYPE OF WORK DRILL DEEPEN PLUG BACK						6. IF INDIAN, ALLOTTED OR TEIBE NAME 7. UNIT AGREEMENT NAME	
b. TYPE OF WELL OIL WELL S CAS WELL OTHER 2. NAME OF OPERATOR FROSTMAN OIL CORP.			SINC ZON	LE MULTIP	8. FARM OR LEASE NAME Federal "D" 9. WELL NO.		
3. ADDRESS OF OPERATOR P. O. DRAWER W, 4. LOCATION OF WELL (Report At surface			any Sta	JUL 22'88		1 10. FIELD AND POOL, OF Square Lake Gr 11. ERC., T., E., M., OF H AND SURVEY OF AR	ayburg San
At proposed prod. Zone & 990' FSL 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN			WN OR POST OFFICE			27, T-16S, R-30E 12. COUNTY OF PARISH   13. STATE	
15. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, (Also to Desrest drig, un) 18. DISTANCE FROM FROFOSED	t line, if any) LOCATION <sup>®</sup>			OF ACRES IN LEASE	TO T	Eddy of Acres Assigned His Well	NM
TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 21. ELEVATIONS (Show whether DF, RT, GR, etc.) 3767.766						22. APPROX. DATE WORK WILL START*	
23. 	BIZE OF CABING	PROPOSED CASIN		CEMENTING PROGRA	M 	QUANTITY OF CEMEN	IT
We propose to do the following work on this well: 1. Set cast iron bridge plug at 2850' above Premier Zone. 2. Perforate the Penrose formation 2256' to 2270'. 3. Stimulate with acid and water sand frac. 4. Dig small work-over pit.					JUN JUN JUN SAIN 88	RECEIVED	
IN ABOVE SPACE DESCRIBE PRO zone. If proposal is to drill preventer program, if any. 24. SIGNED MACON Karen R. Pe (This space for Federal o	or deepen direction	proposal is to deep ally, give pertinent	data on	ng back, give data on p subsurface locations a Production Cle		ductive sone and propose ed and true vertical depth DATE6/29/	
PERMIT NO.		<u> </u>	,	APPROVAL DATE		DATE 7-2	1-58

•

## \*See Instructions On Reverse Side