

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Marbach Energy Corp</u>		Lease <u>State</u>		Well # <u>4</u>	
Location of Well	Unit P <u>990302</u>	Section <u>28</u>	Township <u>17</u>	Range <u>28</u>	County <u>Eddy</u>
Drilling Contractor <u>Jenkins Bros. &</u>			Type of Equipment <u>Cable tools to start 5-5-75</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
8 7/8"	7"	20"		450	
* 6 3/4"	4 1/2"	14-15		830	Circulate

Casing Data:

Surface 27 joints of 4 1/2 inch 10.5 # Grade APT - J-55
(Approved) (Rejected)

Inspected by Lelan Merriam date 6-13-75

Cementing Program

Size of hole 6 3/4" Size of Casing 4 1/2 Sacks cement required 200

Type of Shoe used ~~Non~~ Float collar used Insert Btm 3 jts welded None

TD of hole 831 Set 829 Feet of 4 1/2 Inch 10.5 # Grade J-55

New-used csg. @ 829 with 100 sacks neat cement around shoe Class C 5" S&H 14.9
+ 100 sax Novo-Lite additives Neat 12.8

Plug down @ 12.50 (AM) (PM) Date 6-13-75

Cement circulated No No. of Sacks None

Cemented by Halliburton Witnessed by Lelan Merriam

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: To be filled to surface with Ready-mix

Top cmt app 90'