

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPER OR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Supersedes C-1
C-102 and C-103
Effective 1-1-65

RECEIVED

JUL 15 1975

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

O. C. C.

ARTESIA, OFFICE

1. Name of Operator Yates Petroleum Corporation ✓	5a. Indicate type of well State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Address of Operator 207 South 4th Street - Artesia, NM 88210	6. State of New Mexico
3. Location of Well UNIT LETTER <u>D</u> <u>1315</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>26</u> TOWNSHIP <u>17S</u> RANGE <u>26E</u> NMPM.	7. Unit Agreement Name Hnulik "EJ" Com.
15. Elevation (Show whether DF, RT, GP, etc.) 3315.7 GR	8. Well No. 1
	9. Field Kennedy Farms Morrow
	10. Depth Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT LOG <input type="checkbox"/> OTHER <u>Set 4 1/2" Prod. Casing</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated completion date, and proposed work) SEE RULE 1103.

TD 8850'; PBTD 8700'. Ran 235 jts of 4 1/2" casing as follows: 70 jts 4 1/2" 11.6# K-L (2280'), 117 jts 4 1/2" 10.5# K-L (4860'); 48 jts. 4 1/2" 11.6# (1546') (Total 8686') set at 8700' KB w/Guide shoe, Float Collar and Automatic fill set at 8664' KB, centralizers at 8630', 8530', 8465', 8338, 8207'. Cemented w/500 gallons mud flush, 295 sacks Class "H" 1/2% CFR-2, 5# KCL, displaced w/40 bbls KCL and 98 bbls fresh water. PD 12:30 PM 7-8-75. Tested casing to 1500#. OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie L. Gressett TITLE Engineer DATE 7-14-75

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUL 17 1975

CONDITIONS OF APPROVAL, IF ANY: