DISTRIBUTION		Form C-103 Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE		
U.S.G.S.	RECEIVE	E D 5a. Indicate Type of Lease
LAND OFFICE		State Fee X
OPERATOR	JUL 1 0 1975	
		<i>,</i>
(DO NOT USE THIS FORM FOR PRI USE "APPLICAT	Y NOTICES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENCE CLOC. ION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS ARTESIA, OFFICE	
OIL GAS KAS WELL	OTHER-	7. Unit Agreement Name
Hondo Drilling Compa	ny 🗸	8. Farm or Lease Name SYN-COMM.
Drawer 2516, Midland	, Texas 79701	9. Well No.
I. Location of Well UNIT LETTER	650 North 2310 FEET	10, Field and Pool, or Wildcat Wildcat
THE West LINE, SECTI	5 TOWNSHIP 17-S RANGE 26-E	
	15. Elevation (Show whether DF, RT, GR, etc.) 3366' GL	12. County Eddy
In. Check	Appropriate Box To Indicate Nature of Notice, Report or	Other Data
		JENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	
	OTHER	
OTHER		······································
		• · · · · · · · · · · · · · · · · · · ·
17. Describe Proposed or Completed O work) SEE RULE 1 103.	perations (Clearly state all pertinent details, and give pertinent dates, inclu	uding estimated date of starting any proposed
-4-75 Drilled 17-1/2 set at 410 fee at 11:00 A.M. 30 minutes with -5-75 Drilling 12-1/2 -6-75 Drilling 11" h -7-75 1401 feet total Spotted 60 gal casing free at 24 lb. and 3 j Howco Reg. with 2% calcium chl 18 hrs. Blowo	ry Tools, spudded 17-1/2" hole at 3:00 P. hole to 411 feet, Ran 9 joints 13-3/8" 4 c, cemented with 425 sacks Class "C", 2% of Cement circulated. Tested 13-3/8" casing nout pressure drop, commenced drilling plu the hole at 834 feet at 8:00 A.M. ble at 1340 feet at 8:00 A.M. depth 11" hole, Running 8-5/8" casing, a lons Baroid Scot-Free and 75 bbls. diesel 9:00 P.M., 7-7-75. Finished running tota bints 32 lb. 8-5/8" casing, set at 1400 fe to 5 lb. Gilsonite and 1/4 lb. Flocele and pride, cement circulated. Plug down at 1:1 at Preventors equipment was installed, a	48 lb. H-40 ST&C Range 3, calcium chloride, plug dow g to 1000 lb. pressure, ug after 18 hrs. W.O.C. ti stuck same at 1100 ft. fuel. Worked 8-5/8" al of 1420.28 feet, 28 jts t. Cemented with 425 sack 200 sacks Class "C" Neat 15 A.M. 7-8-75. W.O.C. 7-7/8" bit run in hole to
drop.	ressure tested at 1000 lbs. pressure for 3 ' hole at 1650' 8:00 A.M.	50 minutes without pressur
8. I hereby certify that the informatio	above is true and complete to the best of my knowledge and belief.	
ANO.A	eun President	DATE July 9, 1975
APPROVED BY	usset SUPERVISOR, DISTRICT I	

CONDITIONS	OF	APPROVAL,	IF	ANY