

COPIES RECEIVED	2
DISTRIBUTION	
FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

RECEIVED

DEC 29 1975

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <b>Plug</b>	<b>O. C. C.</b> <b>ARTESIA, OFFICE</b>	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator <b>Hondo Drilling Company</b> ✓		5. State Oil & Gas Lease No.
3. Address of Operator <b>Drawer 2516, Midland, Texas 79701</b>		7. Unit Agreement Name
4. Location of Well UNIT LETTER <b>F</b> <b>1650</b> FEET FROM THE <b>North</b> LINE AND <b>2310</b> FEET FROM <b>West</b> THE LINE, SECTION <b>5</b> TOWNSHIP <b>17-S</b> RANGE <b>26-E</b> NMPM.		8. Farm or Lease Name <b>SYN-Comm.</b>
		9. Well No. <b>1</b>
		10. Field and Pool, or Wildcat <b>Undesignated Morrow</b>
	15. Elevation (Show whether DF, RT, GR, etc.) <b>3366 ft.</b>	12. County <b>Eddy</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-27-75 Drilled to total depth of 8,053 feet 7-7/8" hole.

7-28-75 35 sacks cement plug set from 7900' to 8000'.  
35 sacks cement plug set from 7700' to 7800'.  
35 sacks cement plug set from 7350' to 7450'.  
35 sacks cement plug set from 6925' to 7025'.  
35 sacks cement plug set from 6325' to 6450'.  
35 sacks cement plug set from 4125' to 4225'.  
35 sacks cement plug set from 2100' to 2200'.  
35 sacks cement plug set from 1350' to 1450'.

Weld cap on 8-5/8" casing and regulation marker erected.

*Casing lifted in hole - 13 3/8" - 410' - 42 1/2" x 10' line.  
8 7/8" - 1400' - 62 1/2" " "*

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Bill C. Cattan* TITLE President DATE 12-23-75

APPROVED BY *Leah M. M...* TITLE OIL AND GAS INSPECTOR DATE DEC 29 1975

CONDITIONS OF APPROVAL, IF ANY: