

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

'B*
re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029492-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Robinson Federal

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25, T16S, R31E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Murphy Minerals Corporation

3. ADDRESS OF OPERATOR

**Tom Boyd, Petroleum Building-Twr Suite
Roswell, New Mexico 88201**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

**1650' FWL, 990 FSL
330 FEL, 330 FNL of Unit N**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4168 GL 4177 KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/4/75 Commenced drilling @ 8:00 A.M. 8/3/75. Drilled 11" hole to 438' ran 11 jts. of 8 5/8" (438'), set @ 450' and cemented w/175 sx. Cl. C. cement w/2% CaCl₂. Circulated 30 sx., plugged down 4:30 P.M. 8/3/75 14 hours.

8/9/75 Drilled to 3802'. Picked up core barrell. Cored from 3802' to 3843'.

8/10/75 Core #1 3802-3862, 60'. Rec. 54'. Assume btm. 6' drilled up.

8/11/75 F.T.D. 4050'. Core #2-3970-4012' 42', Rec. 41.6'.

8/12/75 F.T.D. 4050-2°. Ran Compensated Neutron- Fm.Density and Dual Laterolog. Ran 101 jts 4074' of 4 1/2", 10.5# J-55 csg. Set @ 4050' K.B. Cemented w/335 sx. 50-50 Pozmix w/8# salt/sx. Plug down and rig released @ 12:15 A.M. 8/12/75.

RECEIVED

AUG 21 1975

U. C. C.

ARTESIA, OFFICE

RECEIVED

AUG 21 1975

**U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

18. I hereby certify that the foregoing is true and correct

SIGNED

Tom Boyd

TITLE

Agent

DATE

8/19/75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED

AUG 20 1975

**R. L. BEEKMAN
DISTRICT ENGINEER**

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U S G O V E R N M E N T

PRINTING OFFICE

WASHINGTON, D. C.