

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Charles Pope II</i>		Lease <i>Pope St</i>		Well # <i>1</i>	
Location of Well	Unit <i>B</i>	Section <i>31</i>	Township <i>17</i>	Range <i>28</i>	County <i>El Paso</i>
Drilling Contractor <i>330 SW 1/4, 12th St. FFL</i>			Type of Equipment <i>CT</i>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>8"</i>	<i>7</i>	<i>24</i>	<i>Used</i>	<i>400</i>	<i>Full</i>
<i>6 1/4"</i>	<i>4 1/2" x 5 1/2"</i>	<i>11.25 lbs</i>	<i>Used</i>	<i>600</i>	<i>Cement</i>
Casing Data:					
Surface <i>21</i> joints of <i>5 1/2</i> inch <i>13.50</i> # Grade <i>Level FFL K-50</i>					
(Approved) (Rejected)					
Inspected by <i>William McLean</i> date <i>11-5-78</i>					
Cementing Program					
Size of hole <i>8 1/4"</i> Size of Casing <i>5 1/2</i> Sacks cement required <i>120</i>					
Type of Shoe used <i>None</i> Float collar used <i>1000</i> Btm 3 jts welded <i>None</i>					
TD of hole <i>600</i> Set <i>600</i> Feet of <i>5 1/2</i> Inch <i>13.50</i> # Grade <i>K-50</i>					
New-used csg. @ <i>650</i> with <i>100</i> sacks neat cement around shoe					
+ <i>sax</i> additives <i>50-50</i> <i>Poz 27000</i> <i>14.0</i> #					
Plug down @ <i>2:30</i> (AM) (PM) Date <i>11-5-78</i>					
Cement circulated <i>No</i> No. of Sacks <i>120</i>					
Cemented by <i>William McLean</i> Witnessed by <i>William McLean</i>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <i>cut came within 60' of surface then full back. Hole will be filled to surface and ready to plug.</i>					