a 3160-5 UNITEL JTATES	MM ATT. CONS COMMISSION
a 3160-5 UNITED JIATES	NN OIL CONS CONNISSION
c 1990) DEPARTMENT OF THE INTERIO	ArteBudgt BuNN N68819135
BUREAU OF LAND MANAGEMEN	
	LC-026874F
SUNDRY NOTICES AND REPORTS ON	WELLS 6. If Indian, Allottee or Tribe Name
o not use this form for proposals to drill or to deepen or ree Use "APPLICATION FOR PERMIT" for such	ntry to a different reservoir. n proposals
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
ype of Well	
Oil Cas Other	8. Well Name and No. Fasken-Exxon AOF Fed Com
anne of Operator YATES PETROLEUM CORPORATION (50	5) 748–1471) 9. API Well No.
ddress and Celephone No.	30-015-21595
105 South 4th St., Artesia, NM 88210	10. Field and Pool, or Exploratory Area
ocation of Well (Footage, Sec., T., R., M., or Survey Description)	(Unstruct L MUSE) Und. Red Lake Penn Gas
980' FSL & 1980' FEL of Section 31-T17S-R27E	(Unit J, NWSE)
	Eddy Co., NM
CHECK APPROPRIATE BOX(s) TO INDICATE N	
	TYPE OF ACTION
	donment Change of Plans
	ging Back Non-Routine Fracturing Ng Repair Water Shut-Off
	ring Casing Conversion to Injection
X Othe	r Add perforations & Dispose Water
	acidize (Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form )
give subsurface locations and measured and true vertical depths for all markers and	inent dates, including estimated date of starting any proposed work. If well is directionally drilled,
<pre>give subsurface locations and measured and true vertical depths for all markers and 1-16-95 - Moved in pulling unit. 1-17-95 - Rigged up wireline. TIH and set so with wireline. Rigged down wireline. Loade Shut down. 1-18-95 - Rigged up pulling unit. Bled well Nippled down wellhead and installed BOP. Ge bbls 2% KCL water. TOOH with 2-7/8" tubing and perforated 9016-9033' w/36 .42" holes (2 and rigged down wireline. TIH w/RBP, ball of 9035'. Set packer at 8911'. Removed BOP an 1000 psi. Swabbing. Shut well in. 1-19-95 - Acidized perforations 9016-9033' w scf/bbl nitrogen and ball sealers. Opened w 1-20-95 - Flow test well. Load tubing with 80 bbls 2% KCL water. Unset RBP. TOOH with tubing Get on on/off tool on packer at 900.</pre>	Completion or Recompletion Report and Log (orm ) inent dates, including estimated date of starting any proposed work. If well is directionally drilled, rones pertinent to this work.)* Standing valve in 1.81" profile at 9060'. TOOH ed 2-7/8" tubing with 50 bbls 2% KCL water. L down. Loaded tubing with 3 bbls 2% KCL water. L down. Loaded tubing with 3 bbls 2% KCL water. et off on/off tool and reverse hole with 100 . Rigged up wireline. TIH with 4" casing guns 2 SPF - Morrow Sand). TOOH with casing gun catcher, packer and 2-7/8" tubing. Set RBP at nd nippled up wellhead. Pressured annulus to with 1000 gallons 7-1/2% Morrow acid with 1000 well on 3/8" choke and flow test. 2% KCL water. Unset packer. Reverse hole with h 2-7/8" tubing, packer and RBP. TIH with 2-7/8
give subsurface locations and measured and true vertical depths for all markers and 1-16-95 - Moved in pulling unit. 1-17-95 - Rigged up wireline. TIH and set so with wireline. Rigged down wireline. Loade Shut down. 1-18-95 - Rigged up pulling unit. Bled well Nippled down wellhead and installed BOP. Ge bbls 2% KCL water. TOOH with 2-7/8" tubing and perforated 9016-9033' w/36 .42" holes (2 and rigged down wireline. TIH w/RBP, ball of 9035'. Set packer at 8911'. Removed BOP and 1000 psi. Swabbing. Shut well in. 1-19-95 - Acidized perforations 9016-9033' wireline. 1-20-95 - Flow test well. Load tubing with 80 bbls 2% KCL water. Unset RBP. TOOH with tubing. Get on on/off tool on packer at 90 Removed BOP. Nippled up wellhead. Pressur down. The	acturize completion or Recompletion Report and Log (orm) inent dates, including estimated date of starting any proposed work. If well is directionally drilled, rones pertinent to this work.)* estanding valve in 1.81" profile at 9060'. TOOH ed 2-7/8" tubing with 50 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 4 " casing guns 2 SPF - Morrow Sand). TOOH with casing gun catcher, packer and 2-7/8" tubing. Set RBP at and nippled up wellhead. Pressured annulus to with 1000 gallons 7-1/2% Morrow acid with 1000 well on 3/8" choke and flow test. 2% KCL water. Unset packer and RBP. TIH with 2-7/8 49'. Unset packer. Reset packer at 8911'. ed annulus to test packer to 1000 psi. Shut Date Jan. 20, 1995
give subsurface locations and measured and true vertical depths for all markets and 1-16-95 - Moved in pulling unit. 1-17-95 - Rigged up wireline. TIH and set as with wireline. Rigged down wireline. Loade Shut down. 1-18-95 - Rigged up pulling unit. Bled well Nippled down wellhead and installed BOP. Ge bbls 2% KCL water. TOOH with 2-7/8" tubing and perforated 9016-9033' w/36 .42" holes (% and rigged down wireline. TIH w/RBP, ball of 9035'. Set packer at 8911'. Removed BOP and 1000 psi. Swabbing. Shut well in. 1-19-95 - Acidized perforations 9016-9033' wireline. 1-19-95 - Flow test well. Load tubing with 80 bbls 2% KCL water. Unset RBP. TOOH with tubing. Get on on/off tool on packer at 90 Removed BOP. Nippled up wellhead. Pressur down. The	acturize completion or Recompletion Report and Log (orm ) inent dates, including estimated date of starting any proposed work. If well is directionally drilled, rones pertinent to this work.)* Standing valve in 1.81" profile at 9060'. TOOH ed 2-7/8" tubing with 50 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. et off on/off tool and reverse hole with 100 . Rigged up wireline. TIH with 4" casing guns 2 SPF - Morrow Sand). TOOH with casing gun catcher, packer and 2-7/8" tubing. Set RBP at hd nippled up wellhead. Pressured annulus to with 1000 gallons 7-1/2% Morrow acid with 1000 well on 3/8" choke and flow test. 2% KCL water. Unset packer. Reverse hole with h 2-7/8" tubing, packer and RBP. TIH with 2-7/8 49'. Unset packer. Reset packer at 8911'. ed annulus to test packer to 1000 psi. Shut
give subsurface locations and measured and true vertical depths for all markers and 1-16-95 - Moved in pulling unit. 1-17-95 - Rigged up wireline. TIH and set so with wireline. Rigged down wireline. Loade Shut down. 1-18-95 - Rigged up pulling unit. Bled well Nippled down wellhead and installed BOP. Ge bbls 2% KCL water. TOOH with 2-7/8" tubing and perforated 9016-9033' w/36 .42" holes (% and rigged down wireline. TIH w/RBP, ball of 9035'. Set packer at 8911'. Removed BOP and 1000 psi. Swabbing. Shut well in. 1-19-95 - Acidized perforations 9016-9033' wireline. 1-20-95 - Flow test well. Load tubing with 80 bbls 2% KCL water. Unset RBP. TOOH with tubing. Get on on/off tool on packer at 90 Removed BOP. Nippled up wellhead. Pressur down. The	acturize completion or Recompletion Report and Log (orm) inent dates, including estimated date of starting any proposed work. If well is directionally drilled, rones pertinent to this work.)* estanding valve in 1.81" profile at 9060'. TOOH ed 2-7/8" tubing with 50 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 4 " casing guns 2 SPF - Morrow Sand). TOOH with casing gun catcher, packer and 2-7/8" tubing. Set RBP at and nippled up wellhead. Pressured annulus to with 1000 gallons 7-1/2% Morrow acid with 1000 well on 3/8" choke and flow test. 2% KCL water. Unset packer and RBP. TIH with 2-7/8 49'. Unset packer. Reset packer at 8911'. ed annulus to test packer to 1000 psi. Shut Date Jan. 20, 1995
give subsurface locations and measured and true vertical depths for all markers and 1-16-95 - Moved in pulling unit. 1-17-95 - Rigged up wireline. TIH and set so with wireline. Rigged down wireline. Loade Shut down. 1-18-95 - Rigged up pulling unit. Bled well: Nippled down wellhead and installed BOP. Get bbls 2% KCL water. TOOH with 2-7/8" tubing and perforated 9016-9033' w/36 .42" holes (2 and rigged down wireline. TIH w/RBP, ball of 9035'. Set packer at 8911'. Removed BOP and 1000 psi. Swabbing. Shut well in. 1-19-95 - Acidized perforations 9016-9033' with scf/bbl nitrogen and ball sealers. Opened with 80 bbls 2% KCL water. Unset RBP. TOOH with tubing. Get on on/off tool on packer at 90 Removed BOP. Nippled up wellhead. Pressur down. The	acturize completion or Recompletion Report and Log (orm) inent dates, including estimated date of starting any proposed work. If well is directionally drilled, rones pertinent to this work.)* estanding valve in 1.81" profile at 9060'. TOOH ed 2-7/8" tubing with 50 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. I down. Loaded tubing with 4 " casing guns 2 SPF - Morrow Sand). TOOH with casing gun catcher, packer and 2-7/8" tubing. Set RBP at and nippled up wellhead. Pressured annulus to with 1000 gallons 7-1/2% Morrow acid with 1000 well on 3/8" choke and flow test. 2% KCL water. Unset packer and RBP. TIH with 2-7/8 49'. Unset packer. Reset packer at 8911'. ed annulus to test packer to 1000 psi. Shut Date Jan. 20, 1995
<pre>give subsurface locations and measured and true vertical depths for all markets and 1-16-95 - Moved in pulling unit. 1-17-95 - Rigged up wireline. TIH and set s with wireline. Rigged down wireline. Loade Shut down. 1-18-95 - Rigged up pulling unit. Bled well Nippled down wellhead and installed BOP. Ge bbls 2% KCL water. TOOH with 2-7/8" tubing and perforated 9016-9033' w/36 .42" holes (2 and rigged down wireline. TIH w/RBP, ball 9035'. Set packer at 8911'. Removed BOP and 1000 psi. Swabbing. Shut well in. 1-19-95 - Acidized perforations 9016-9033' wirelines. 1-20-95 - Flow test well. Load tubing with 80 bbls 2% KCL water. Unset RBP. TOOH with tubing. Get on on/off tool on packer at 90 Removed BOP. Nippled up wellhead. Pressur down. 1 trues, and the long of the state office use) Approved by Condition: of approval, if any: Approved by Condition: of approval, if any: Condition: of approval, if any: Condition: of approval, if any: Condition: of approval, if any: Condition: State office use Condition: Condition: State office use Condition: Condition: Cond</pre>	acturize Completion or Recompletion Report and Lyg(erm) inent dates, including estimated date of starting any proposed work. If well is directionally drilled, rones pertinent to this work.)* estanding valve in 1.81" profile at 9060'. TOOH ed 2-7/8" tubing with 50 bbls 2% KCL water. I down. Loaded tubing with 3 bbls 2% KCL water. et off on/off tool and reverse hole with 100 . Rigged up wireline. TIH with 4" casing guns 2 SPF - Morrow Sand). TOOH with casing gun catcher, packer and 2-7/8" tubing. Set RBP at nd nippled up wellhead. Pressured annulus to with 1000 gallons 7-1/2% Morrow acid with 1000 well on 3/8" choke and flow test. 2% KCL water. Unset packer. Reverse hole with h 2-7/8" tubing, packer and RBP. TIH with 2-7/8 49'. Unset packer. Reset packer at 8911'. ed annulus to test packer to 1000 psi. Shut ACCEPTED FOR ACCEPTED FOR ACCEPTED FOR