NO. OF COPIES RECEIVED	·				Form C+103 ~ Supersedes Old
DISTR BUTION					C+102 and C-103
SANTA FE		NEW MEXICO OIL CONSE		•	Effective 1-1-65
FILE			BEC	EIVED	5a, Indicate Type of Lease
U.S.G.\$.			Ed pro ma		State Fee X
LAND FICE			*101/	6 1975	5. State Oil & Gas Lease No.
OPER OR			NUV	6 13/3	
	SUNDRY	NOTICES AND REPORTS ON	WELLS	- C	William Illini
(DO NOT USE THIS FOR USE *	M FOR PROPO	NOTICES AND REPORTS ON DEALS TO DRILL OR TO DELPEN OF FLUG 64 N FOR PERMIT - " (FORM C-101) FOR SUC)	CK TO A DIFFERENT RE	SCAVOR!	
GAS	£.)		A(1)	•	7. Unit Agreement () me
me of Operator		OTHER-			8. Form of Lease Name
Yates Petroleum Corporation					Patterson "EL"
3. Address of Operator					9. Well No.
207 South 4th Street-Artesia, NM 88210					1
4. Location of Well					10. Field Pool, or Wildrat
UNIT LETTER M	Wildcat				
THE West	INE, SECTION	31 TOWNSHIP 175	RANGE 26	E NMPM	
15. Elevation (Show whether DF, RT, GE, etc.) 3442' GR					12. County Eddy
$\frac{1}{16}$	777777	7////		D 0	
•		ppropriate Box To Indicate N	ature of Notice,		
NOTIC	E OF INT	TENTION TO:		SUBSEQUEN	T REPORT OF:
	1	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CAS 16
PERFORM REMEDIAL WORK	1	PEDG AND ABANDON	COMMENCE DRILLING	OPNS.	PLUG ARAN JONMENT
PULL OR ALTER CASING	†	CHANGE PLANS	CASING TEST AND CE	MENT JOS	Construction of the Constr
POLL OR ALIER CASING	j		OTHER Perf	orate and	d treat X
OTHER					
				dance industry	actualists of the second secon
17. Describe Proposed or Conwork) SEE RULE 1103.	mpleted Ope	rations (Clearly state all pertinent deta	uts, and give perioner	r dires, increire	estimated a comproposed
Moyod in Co	omnlet	ion unit rigged un	and set pa	cker at 8	3060' and perforated
the Strawn	forma	tion at 8092-8096' v	√/17 .45" i	et shots	. Acidized perforatio
71000 as1	lone	5% DS-30 acid and N:	itrogen. B	lew back	treatment and re-
w/1000 gai.	11	show of gas and salf	twater S	trabbed s	alt water and small
		show of gas and sax	· water .	,,assea s	
show of ga	5. nl	at 8080' w/2 sacks	of domont o	TOOG ba	PTH w/tubing and
Set Bridge	Plug	at 8080' W/2 sacks (or cement a	hata and	9024_30! w/24 45"
packer and	perfo	rated 8002-08' w/24	.45" jet s	snots and	
shots. Se	t pack	er at 7920' and acid	dized w/400	gallon:	s of 15% DS-30 acid.
Treated pe	rforat	ions 8002-8008' and	8024-8030'	w/12000	gallons Dalotrol
acid and 3	000 ga	llons of CO2. After	r cleaning	up well	flowed 1320 MCFPD.
FTP 215# o					
•.					
				-	
18. I hereby certify that the	information	pove is true and complete to the best	my towledge and	beila.	
C_{1}	/	. (_		3 5 5 55
SIGNED Zddiel	116	Manfield TITLE	Engineer		11-5-75
	7				<u> </u>
11/	7 U.			TDICT II	NOV 7 1975
111 (1	, XM	MIN TITLE ST	JPERVISOR, DIS	I MULT LE	DATE HUT IN IN IN

CONDITIONS OF APPROVAL, IF ANY: