

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 7833	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka 8188	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 826	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta 2220	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo 4206	T. Bone Springs	T. Wingate	T.
T. Wolfcamp 5381	T. Mrow Clastics 8383	T. Chinle	T.
T. Penn.	T. Chester 8586	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	360	360	Surface & gravel				
360	843	483	Red bed and lime				
843	1300	457	Anhy and lime				
1300	2837	1537	Anhy				
2837	3218	381	Lime and dolomite				
3218	4172	954	Lime				
4172	4832	660	Lime and dolomite				
4832	7890	3058	Lime				
7890	8354	464	Lime and shale				
8354	8405	51	Lime				
8405	8640	235	Lime and shale				