

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND	FICE
OPER	OR

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

Form C-103
Supersedes Old
C-102 and C-104
Effective 1-1-65

AUG 22 1975

SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)		5a. Indicate Type of State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>	
1. Name of Operator Yates Petroleum Corporation		7. Unit Agreement Name	
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		8. Form of Lease Name City of Artesia EQ Com	
4. Location of Well UNIT LETTER J, 1650 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 17S RANGE 25E NMPM.		9. Well No. 1	
15. Elevation (Show whether DF, RT, GP, etc.) 3450' GR		10. Field Und. Morrow	
12. County Eddy			

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CEMENT <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

Spudded a 17½" hole at midnight 8-16-75.
TD 370'. Ran 11 jts of 13-3/8" 48# (351') set at 369' KB. Cemented w/250 sacks of Class C 4% CaCl. Cement circulated. PD 12:45 PM 8-17-75. WOC 12 hours. NU and drilled cement, reduced hole to 12¼" and resumed drilling.
TD 1264' - Ran 31 joints of 8-5/8" 24#, J-55 new casing (1264') set at 1262' KB w/Tex-Pattern notched shoe, 2 centralizers at 1220 & 767', 2 baskets at 810 & 698'. Cemented w/450 sacks Incor mix (6% Gilsonite 0.6% flocele) 2% CaCl + 250 sacks Class C 2% CaCl. PD 12:10 PM 8-19-75. Cement did not circulate. WOC 7 hours ran Temperature Survey, found top of cement at 475'. Ran 1" tubing, tagged firm cement at 485'. Spotted 100 sacks Class C 4% CaCl PD 8:30 PM 8-19-75. WOC 2-3/4 hrs, tagged cmt at 475'. Sptd 150 sx Class C 4% CaCl at 442'. PD 11:45 PM 8-19-75. WOC 2¼ hrs, cut off 13-3/8" casing, strapped to 8-5/8" csg, cut off 8-5/8" and welded on bell nipple. Ran 1" tbg and tagged cement at 430'. Spotted 100 sacks Class C 4% CaCl. PD 2:50 AM 8-20-75. WOC 3 hrs. & tagged cement at 371'. Circ. hole w/275 sx Class C 4% CaCl. PD 6:40 AM 8-20-75. WOC 18 hrs. Finished NU, installed BOP's & tstd to 1000#. OK. Drld cmt & tstd to 600#. OK. Reduced hole to 7-7/8" & resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Eddie M. [Signature]</u>	TITLE <u>Engineer</u>	DATE <u>8-22-75</u>
APPROVED BY <u>W.A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>AUG 22 1975</u>

CONDITIONS OF APPROVAL, IF ANY: