

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Betrice Beddingfield</u>		Lease <u>state</u>		Well # <u>7</u>	
Location of Well	Unit <u>360 S 455 W</u>	Section <u>36</u>	Township <u>17</u>	Range <u>27</u>	County <u>Elky</u>
Drilling Contractor <u>Artesia Fishing tool Co.</u>			Type of Equipment <u>Rotary & start 9-10-75</u>		

9 1/2" hole to 300'
reduce to 7 7/8"

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>9 1/2" + 7 7/8"</u>	<u>5 1/2"</u>	<u>14</u>	<u>used</u>	<u>1375</u>	<u>200 cwt.</u>

Casing Data:

Surface 41 joints of 5 1/2 inch 20 # Grade J-55 USED.

(Approved) (~~Rejected~~) VERY GOOD CONDITION

Inspected by Leon Bergstrom date 9-21-75

Cementing Program

Size of hole 7 7/8 Size of Casing 5 1/2" Sacks cement required 237 cwt.

Type of Shoe used Float Float collar used NONE Btm 3 jts welded NO

TD of hole 1366 Set 1361 Feet of 5 1/2 Inch 20 # Grade J-55 GOOD.

~~New~~-used csg. @ 1358 HR with 150 sacks neat cement around shoe 1.32 cwt/ft YIELD

+ 300 sack DOWELL LITE additives 2% CaCl₂ 1.65 cwt/ft YIELD

Plug down @ 12⁵⁰ (~~PM~~) (PM) Date 9-21-75

Cement circulated YES No. of Sacks BARELY FILLED SMALL CELLAR

Cemented by DOWELL Witnessed by Leon Bergstrom

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: