

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND	FICE
OPER	OR

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
OCT 14 1975

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Smith "EB"
9. Well No. 1
10. Field, Pool, or Wildcat Eagle Creek (S.A.)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well OIL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 South 4th Street - Artesia, NM 88210
4. Location of Well UNIT LETTER F 1650 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 13 TOWNSHIP 17S RANGE 25E NMPM.
15. Elevation (Show whether DF, RT, GP, etc.) 3466 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING Casing <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated cost of any proposed work) SEE RULE 1103.

Spudded 14-3/4" hole at 6:15 PM 10-1-75.
Ran 16 joints of 10-3/4" (312') 32# used casing set at 325' KB. Cemented w/250 sacks Class "H" 4% CaCl. Cement circulated. PD 9:00 AM 10-2-75. Cement fell back. Filled hole to surface with 1 yard of Ready mix. WOC 12 hours. Backed off landing joint, drilled plug and resumed drilling a 9-7/8" hole. TD 1212'- Ran 39 joints of 7" 20# J-55 (1215') of used casing. 1-Texas Pattern Shoe, 2 centralizers and baskets at 750-689'. Cemented w/350 sacks Incor mix (6% gilsonite, 0.6% flocele, 2% CaCl) and 150 sacks Class "C" 2% CaCl. PD 8:45 AM 10-5-75. Cement did not circulate. WOC 6 hours. Ran Temp Survey and ran 1" tubing and washed to 504'. Spotted 100 sacks Class C 4% CaCl. PD 5:30 PM 10-5-75. WOC 3 hours, tagged cement at 378'. Spotted 75 sacks Class "C" 4% CaCl. PD 9:00 PM 10-5-75. WOC 2 hours, tagged cement at 309' and spotted ¹⁸⁰25 sacks. Cement circulated. PD 11:45 PM 10-5-75. WOC 18 hours tacked 10-3/4" to 7", cut off landing joint, welded on bell nipple, installed BOP's and tested to 1500#. OK. Drilled plug and tested shoe to 600#. OK. Reduced hole to 6 1/4" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief

SIGNED Christine Johnson TITLE Geol. Secretary DATE 10-10-75
APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE OCT 14 1975
CONDITIONS OF APPROVAL, IF ANY: