

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYIN. M. D. C. C. COPY
SUBMIT IN TRIPLI
(Other instructions
verse side)TE*
FO*Copy 65F
Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0219603-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "BW"

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Eagle Creek S.A.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 22-17S-25E

Unit P NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

990' FSL & 990' FEL of Sec. 22-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3520' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☐
☐

REPAIRING WELL

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & Surface Casing

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-18-75 - Spudded a 15" hole at 6:00 PM 10-18-75.

TD 283' - Ran 9 joints of 32# J-55 used casing (292') set at 283' KB. Cemented w/200 sacks of Class C 4% CaCl. PD 7 AM 10-19-75. Cement circulate WOC and cement fell back filled hole w/1½ yards of Ready-mix. WOC 12 hours and backed off landing joint, drilled cement, reduced hole to 9½" and resumed drilling.

TD 1160'. Ran 37 jts of 7" 20# J-55 used casing (1162') set at 1160', 1-Tex Pattern shoe, 2 centralizers, 1 basket at 689' and cemented w/350 sacks of Incor Mix 2% CaCl + 100 sacks of Class C 2% CaCl. PD 8:30 AM 10-21-75. Cement circulated. WOC 18 hours, nipples up and installed BOP's and tested to 1000#. OK. Drilled shoe and tested to 600#. OK. Reduced hole to 6¼" and resumed drilling.

RECEIVED

OCT 22 1975

OCT 24 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Eddie H. [Signature]

TITLE

O. C. C.
ARTESIA, OFFICE

DATE 10-22-75

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

OCT 25 1975

G. L. BEEKMAN
ACTING DISTRICT ENGINEER