

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates Pet Corp.</u>		Lease <u>Lowers FB Com.</u>		Well # <u>1</u>	
Location of Well	Unit <u>E</u> <u>1980N 66W</u>	Section <u>34</u>	Township <u>17</u>	Range <u>25</u>	County <u>Elky</u>
Drilling Contractor	<u>And Dily Co</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 7/8" or 12 3/4"</u>	<u>48 or 34</u>		<u>200</u>	<u>cir.</u>
<u>12 1/4"</u>	<u>8 5/8"</u>	<u>24</u>		<u>1180</u>	<u>cir.</u>
<u>7 7/8"</u>	<u>4 1/2" or 5 1/2"</u>	<u>10.5, 11.6, 15.5 or 7</u>		<u>8500</u>	<u>250</u>

Casing Data:

INTER. 28 joints of 8 7/8 inch 24 # Grade K.55 NEW API

(Approved) (~~Rejected~~)

Inspected by Leon Burton date 11-16-75

Cementing Program

Size of hole 12 1/4 Size of Casing 8 7/8 Sacks cement required

Type of Shoe used TEXAS Float collar used INSERT Btm 3 jts welded THREDOLOK

TD of hole 1198 Set 1229 Feet of 8 7/8 Inch 24 # Grade K.55

New-~~used~~ csg. @ 1198 with 150 sacks neat cement around shoe 2% CaCl<sub>2</sub>

+ 400 sax HOWCO LITE additives 5 1/2 lbs. 1/4" FLOCELE & 2% CaCl<sub>2</sub>

Plug down @ 420 (AM) (PM) Date 11-16-75

Cement circulated YES No. of Sacks 75 sx.

Cemented by HALLIBURTON Witnessed by Leon Burton

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: