

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt _____
B. Salt _____
T. Yates _____
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres 848
T. Glorieta 2239
T. Paddock _____
T. Blinbry _____
T. Tubb _____
T. Drinkard _____
T. Abo 4211
T. Wolfcamp 5362
T. Penn. _____
T. Cisco (Bough C) 6680

T. Canyon _____
T. Strawn 7580
T. Atoka 7985
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Granite _____
T. Delaware Sand _____
T. Bone Springs _____
T. Morrow 8298
T. Chester 8484
T. _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn. "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Qtzite _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	360	360	Surface, gravel & rock				
360	958	598	Red bed and rock				
958	1286	328	Dolomite				
1286	2865	1579	Lime				
2865	3916	1051	Lime and shale				
3916	4482	566	Lime				
4482	4650	168	Lime and shale				
4650	5120	470	Shale				
5120	5213	93	Lime and shale				
5213	7262	2049	Shale				
7262	7967	700	Lime and shale				
7967	8015	48	Shale and sand				
8015	8323	308	Lime and shale				
8323	8570	247	Lime, shale and sand				

NE Tops
Penn 6702
Strawn 7652
Atoka 8087
Mancos 8240
Clastic 8302