NO. OF COPIES RECEIVED 3					Form C-103	J.	
DISTRIBUTION					Supersedes Oli C-102 and C-103		
SANTA FE	NEW	NEW MEXICO OIL CONSERVATION COMMISSION				55	
FILE I V			r		a. Indicate Type	of Leuse	
U.S.G.S.				1	State	Fee X	
LAND TICE			RECE	IVED			
OPEF TOR	}				,,		
SUN (DO NOT USE THIS FORM FOR USE "APPLI	DRY NOTICES A	ND REPORTS ON V	VELLS DEC. 1.5	1975			
OIL ARTESIA, OFFICE					7. Unit Agreement 8. Farm or Lease		
Yates Petroleum Corporation 🗸					Johnson "FE"		
Yates Petroleum Corporation V 3. Address of Operator					9. Well No.		
207 South 4th St	treet - Art	esia, NM 88	3210		. 1		
4. Location of Well				· ·	10. Field and Poo	ol, or Wildcat	
UNIT LETTER A	330	North	990	_ FEET FROM _	Eagle Cr	eek S.A.	
East Line. se	23	17S	RANGE 25E	NMPM.			
					12. County	<i>1,1,1,1,1,1,1,1</i> ,1,1,1,1,1,1,1,1,1,1,1,	
	15. El	evation (Show whether I	OF, RT, GR, etc.) GR		Eddy		
16.						(77777777777777777777777777777777777777	
Chec	EK Appropriate D FINTENTION TO		ature of Notice, Reposite	SEQUENT	REPORT OF:		
PERFORM REMEDIAL WORK		PLUG AND ABANDON	REMEDIAL WORK		ALTER	ING CASHIG .	
TEMPORARILY ABANDON		,	COMMENCE DRILLING OPNS.			NE ABANDONMENT	
PULL OR ALTER CASING		CHANGE PLANS	CASING TEST AND CEMENT 3	0,3 A. A			
			OTHER			U	
OTHER							
The Describe Proposed or Complete work) SEE RULE 1103. Since TD 408' - Ran 9 w/250 sx Class drilled cement TD 1170'. Ran CO hole to 1200 notched shoe, comt'd w/350 sx CaCl. PD 12:30 cmt. at 680'. CaCl. PD 8:30 A C 4% CaCl. PD PD 3:00 PM 12-3 6 PM 12-3-75. w/9½ yards of Ron collars, Nip cement and test	jts of 10-C 4% CaCl. plug and re 12 jts of 7 1. Ran 31 entralizers Incor mix AM 12-3-75. Ran 1", una M 12-3-75. woc 12-3-75. woc 2 hrs. eady-mix. epled up and ed shoe to	PD noon 11 educed hole 7" csg, unab jts of 7" 2 and 2 bask (6% gtls + 0. WOC 6 housele to wash WOC 3 hrs, 75. WOC 3 h 2½ hrs, sptd, sptd 75 sx WOC 28 hourd installed 600#. OK.	55 csg. (389') -29-75. Cement to 9-7/8" and le to wash bri O# K-55 new cs ets at 756 & 6 6% flocele 2% rs and ran Tem below 420'. S tagged cmt. a rs, sptd 100 s 75 sx Class C Class C 4% Ca s, cut off lan BOP's, tested Reduced hole	set a circu resume idge at sg (121 577', s CaCl) mp. Sur spotted at 404' sx Clas Clas acl at nding j to 100 to 6%"	t 402' KB lated. W d drillin 570'. Pu 4') w/Tex et casing + 150 sx vey, four 100 sx C , sptd 75 s C 4% Ca Cl at 370 40' and f t., welde 0#. LK. I	OC 12 hrs., IOC 12 hrs., III constant IOC 12 hrs., III constant III	
18. I hereby certify that the information	ation above is true ar	nd complete to the best	f my I nowledge and belief.				
	<i>t</i> .	`			9.	1 11 75	

DEC 15 1975

CONDITIONS OF APPROVAL, IF ANY