

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

DEC 5 1975

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Former Lease Name Gissler AV
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		9. Well No. 12
4. Location of Well UNIT LETTER C 840' FEET FROM THE North LINE AND 2310' FEET FROM THE West LINE, SECTION 23 TOWNSHIP 17S RANGE 25E NMPM.		10. Field and Pool, or Wildcat Eagle Creek S.A.
15. Elevation (Show whether DF, RT, GP, etc.) 3490'		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of any proposed work) SEE RULE 1103.

Spudded 15" hole at 4:30 PM 11-20-75.
Ran 7 joints of 10-3/4" 32# k-55 casing (292') set at 305' KB. Cemented w/ 200 sacks of Class "C" 4% CaCl. PD 6:30 AM 11-21-75. Cement circulated. WOC 12 hours. Backed off landing joint, drilled cement, reduced hole to 9-7/8" and resumed drilling.
TD 1165' - Ran 12 joints of 7" casing, unable to wash in casing at 545'. POOH w/casing. RIH w/bit, mixed mud and reamed to 1191'. Ran 30 joints of 7" 20# new casing (1216') w/notched shoe, 2 centralizers, 2 baskets at 711 & 632', washed in last 100' and cemented w/350 sacks Incor Mix 2% CaCl + 150 sacks Class "C" 2% CaCl. PD 12:45 PM 11-25-75. Set at 1191' KB. WOC 7 hours and ran temp. survey. Top of cement at 400'. Ran 1" tubing, unable to wash below 384'. Spotted 100 sacks Class "C" 4% CaCl. PD 8:25 PM 11-25-75. WOC 3 hours. Tagged cement at 384'. Spotted 150 sacks Class "C" 4% CaCl. PD midnight. WOC 3 hours, tagged cement at 363'. Pulled 1" tubing and filled hole w/100 sacks Class "C" 4% CaCl. + 10 yards of Ready-mix. Completed at 8:45 AM 11-26-75. WOC 18 hours, cut off landing joint, nipped up, instl bop's tstd 1000#.ok.Drld shoe tstd csg to 600#.ok. Rducd hole to 6 1/4" & resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine L. Linder TITLE Geol Secty DATE 12-5-75

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE DEC 8 1975

CONDITIONS OF APPROVAL, IF ANY: