

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

DEC 31 1975

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 South 4th Street - Artesia, NM 88210

4. Location of Well
UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM East LINE, SECTION 15 TOWNSHIP 17S RANGE 26E NMPM.

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name
Caffall "FD"

9. Well No.
1

10. Field, Pool, or Wildcat Und.
Kennedy Farma Morrow

12. County
Eddy

15. Elevation (Show whether DF, RT, GR, etc.)
3337' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
		OTHER 10-3/4" casing <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated dates of any proposed work) SEE RULE 1103.

Spudded a 17 1/2" hole at 10:00 AM 12-15-75.
TD 425' - Ran 13 joints of 13-3/8" 48# H-40 casing (425') and set at 423'. Cemented w/250 sacks of Class "C" 4% CaCl. PD 8:00 PM 12-15-75. WOC and cement fell 30', filled hole w/pea gravel. WOC 12 hours, cut off casing, nipples up, drilled plug, reduced hole to 12 1/4" and resumed drilling.
TD 1409' - Ran 32 joints of 8-5/8" 24# casing w/2 centralizers at 700' and 1370', 1 basket at 660'. Cemented w/400 sacks of Howco-lite, 5# gilsonite, 1/4# flocele 2% CaCl followed w/150 sacks of Class "C" 2% CaCl. PD 3:45 PM 12-17-75. Cement did not circulate. WOC and ran 1", could not get below 182'. Ran Temperature Survey at 9:30 PM 12-17-75, found top of cement at 175'. Dumped 2 yards of Ready-mix and filled hole. JC 1:00 AM 12-18-75. WOC 18 hours. Nipples up, installed BOP's and tested to 1000# OK. Drilled plug and tested to 600#. OK. Reduced hole to 7-7/8" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 12-30-75

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JAN 6 1976

CONDITIONS OF APPROVAL, IF ANY: