

CONTR Ard OFF'S ELEV 3337' GL 3354' KB PD 8900' RT

F.R. 12-22-75  
(Morrow)  
1-8-76 Drlg 8350'  
1-14-76 TD 8670'; "Tight"  
DST (Morrow) 8213-8355', Mis-Run  
2-9-76 TD 8670'; FBD 8550'; Complete  
Perf (Morrow) 8402-16' w/4 SPF  
Natural  
(Morrow) FOUR POINT GAUGES:  
Flwd 1237 MCFGPD, 10/64" chk, 60 mins, TP 2605#  
Flwd 2333 MCFGPD, 17/64" chk, 60 mins, TP 2420#  
Flwd 3590 MCFGPD, 22/64" chk, 60 mins, TP 2077#  
Flwd 4647 MCFGPD, 28/64" chk, 60 mins, TP 1685#  
LOG TOPS: San Andres 948', Glorieta 2357', Abc  
4375', Wolfcamp 5542', Cisco 6600', Canyon 7400'

2-2-5 NM

EDDY  
YATES PETROLEUM CORP.

Kennedy Farms  
1 Caffall "FD" Com.  
Sec 15, T17S, R26E

NM  
Page #2

2-9-76

Continued  
Strawn 7836', Atoka 8197', Morrow Clastics  
8389'

2-14-76

COMPLETION ISSUED

2-2-5 NM  
IC 30-015-70108-75