

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>J.B. Adamson</u>		Lease <u>Collier State</u>		Well # <u>4</u>	
Location of Well	Unit <u>23105 990W</u>	Section <u>27</u>	Township <u>17</u>	Range <u>28</u>	County <u>Eddy</u>
Drilling Contractor <u>Armed</u>			Type of Equipment <u>Cable tools to start 1-8-76</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>8"</u>	<u>7"</u>			<u>518</u>	<u>5+ Pulled</u>
<u>6"</u>	<u>4 1/2"</u>	<u>9.5</u>		<u>840</u>	<u>Circulate</u>

Casing Data:

Surface 24 joints of 4 1/2 inch 9.50# Grade API Used 5-55
(Approved) (~~Rejected~~)

Inspected by Selan G. Morris date 5-1-76

Cementing Program

Size of hole 8 1/2" 6 7/8" 5 1/8" Size of Casing 4 1/2" Sacks cement required 200

Type of Shoe used None Float collar used Insert Btm 3 jts welded None

TD of hole 826' 61" Set 826' Feet of 4 1/2 Inch 9.50# Grade 5-55

New-used csg. @ 826' 61" with 30/30 sacks neat cement around shoe Class C Lite Poz 3, 2% cc #3 sand 4" Cellofane

+ 150/30 sax Class C additives Lite Poz 3, 2% cc #3 sand 4" Cellofane

Plug down @ 2:30 (AM) (PM) Date 5-1-76

Cement circulated No No. of Sacks None

Cemented by Dowell Witnessed by Selan G. Morris

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Cont Top App. 80' Hole will be filled w/Ready Mix
Water 200' Spotted zones from 475 to 500'