

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

NOV 18 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- Dry Hole	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation ✓	5. State Oil & Gas Lease No.
3. Address of Operator 207 South Fourth Street, Artesia, NM 88210	7. Unit Agreement Name
4. Location of Well UNIT LETTER N 330 FEET FROM THE South LINE AND 2310 FEET FROM THE West LINE, SECTION 12 TOWNSHIP 17S RANGE 25E NMPM.	8. Farm or Lease Name Norris "FK"
	9. Well No. 1 1
	10. Field and Pool, or Wildcat Eagle Creek (S.A.)
15. Elevation (Show whether DF, RT, GR, etc.) 3454'GR; 3467'KB	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

11. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has been temporarily abandoned since July, 1976. We now propose to plug the well by setting a wireline bridge plug @ 1350'KB, then dump about 35' cement on top of the plug, fill hole w/heavy mud and set dry hole marker in cement plug at surface.

11. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ed M. Lutz TITLE Engineer DATE 11-17-76

APPROVED BY W. A. Gessett TITLE SUPERVISOR, DISTRICT II DATE NOV 19 1976

CONDITIONS OF APPROVAL, IF ANY:

Notify N.M.O.C.C. in sufficient time to witness

Plugging