

NO. OF COPIES RECEIVED		3
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPER OR		

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

FEB 25 1976

O. C. C.

SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OILER. IT IS TO BE USED TO A DIFFERENT EXTENT. USE "APPLICATION FOR PERMIT TO DRILL OR TO OILER" (FORM O-100) FOR SUCH PROPOSALS.)

<input type="checkbox"/> LL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		5a. Indicate Type of Well <input type="checkbox"/> Oil <input checked="" type="checkbox"/> Gas
1. Name of Operator Yates Petroleum Corporation		6. Field Name Sweet-Yates "FM" Com
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		7. Unit Agreement 1
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>25</u> TOWNSHIP <u>17S</u> RANGE <u>26E</u> NMPN.		8. Field Name Und. Kennedy Farms
15. Elevation (Show whether DF, RT, GR, etc.) 3295' GR		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>		SUBSEQUENT REPORT OF: PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> OTHER <u>Change Name of Lease</u> <input checked="" type="checkbox"/>
--	--	---	---

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, to the extent possible.) SEE RULE 1103.

To change the name of Lease from Sweet "FM" Com #1 to Sweet-Yates "FM" Com #1

Spudded a 17½" hole at 7:00 PM 2-17-76. Drilled to 291' and ran 7 joints of 13-3/8" 48# K-55 (290.81') set at 289' and cemented w/200 sacks of Class "C" 4% CaCl. PD 12:30 AM 2-18-76. WOC. and cement dropped, filled hole w/4 yards of Ready-mix. WOC 12 hours, nipples up, cut of landing joint, drilled plug, reduced hole to 12½" and resumed drilling. TD 1385'. Ran 34 joints of 8-5/8" 24# K-55 ST&C (1409.90'), 1-Tex Pattern Shoe, centralizers at 1344 and 888', baskets at 928 and 845' set at 1385'KB. Cemented by Halliburton w/500 sacks of Lite-Wt 5# gilsonite/sx & 1/4# flocele/sx, followed w/150 sacks of Class "C" 2% CaCl. PD 3:30 PM 2-20-76. Cement circulated. WOC 18 hours, nipples up, installed BOP's and tested to 1000#. OK. Drilled plug and tested casing to 600#. OK. Reduced hole to 7-7/8" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 2-24-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE FEB 26 1976

CONDITIONS OF APPROVAL, IF ANY: